



# QUICSEAL 711

Product Name

## DPC

BS 6398 Class B fibre based damp proof course.

### Description

QUICSEAL 711 is a continuous sheet damp-proof course material used to provide a barrier to the passage of water or water vapour from the external to the internal part of the building. Manufactured from a composition of a fibre base saturated and coated in high penetration grade bitumen, QUICSEAL 711 is capable of withstanding imposed loads (up to 0.10 N/mm<sup>2</sup>) applied by brickwork, blockwork or stonework walls.

### Uses & Advantages

- Prevents rising water under medium imposed loads when applied horizontally as a damp proof course
- Economical and environmentally friendly; does not contain pitch or plasticisers
- Cold-applied system – Easy to install
- Flexible
- Complies to BS 6398 Class B
- High compatibility with majority of adjacent materials, including insulation materials, tanking and damp proof membranes.
- Forms an effective barrier against the capillary rise of water when used in accordance to the recommendations of British Standards CP 102: 1973 Code of Practice for protection of buildings against water from the ground.

### Technical Data

Weight	:	3.3 kg / sq metre nominal
Compressive stress	:	Up to 1 N/mm <sup>2</sup>
Tensile stress MD/CD	:	0.881 / 0.454
% Elongation MD/CD	:	6.88 / 23.03 %

## **Application Directions**

Installation of QUICSEAL 711 can be carried out in all weather conditions.

### *Damp-proofing of Floors and Walls*

Prepare an even bed of mortar to receive QUICSEAL 711. Ensure that QUICSEAL 711 is extended through the thickness of the wall including pointing, applied rendering or other facing material.

Where perforated brickwork is used, ensure that adjacent perforations are filled with mortar completely. All overlaps should be 100mm and sealed with hot poured bitumen or bitumen lap cement. On walls, QUICSEAL 711 shall have a minimum upturn of 150mm above the adjoining external ground level.

## **Health & Safety**

QUICSEAL 711 is non-hazardous to health when used as a damp proof course or membrane.

## **Packing**

QUICSEAL 711 is supplied in rolls of 8m length by 1m width.

### Important Notes

The information set forth herein is furnished free of charge in good faith and is based on technical data that QUICSEAL considers to be reliable. This information is intended for use by persons having technical skill and at their own discretion and risk. Information contained in this product sheet conforms to the standard detail recommendations and specifications for the installation of QUICSEAL products as of the date of publication of this document. QUICSEAL makes no other warranties and assumes no liability, expressed or implied, as to the architecture, engineering or workmanship of any project. To ensure that you are using the latest, most complete information, please contact QUICSEAL.

Reference No. QS 711/ 9/99

**QUICSEAL CONSTRUCTION CHEMICALS PTE LTD**

*QUICSEAL – the professional's choice of quality products and systems for building construction*