



# QUICSEAL 108

Product Name

**SuperSeal**

## Description

QUICSEAL 108 is a colourless sealer for ceramic tiles, natural stones, concrete, masonry and brickwork surfaces for both internal and external applications. It comprises of a special blend of selected resins, which waterproofs and improves substrate and finished surfaces against weathering, abrasion and water seepage.

## Uses

- For protection of wood, stones, marble, granites, concrete, glass, polycarbonate, ceramics, etc.
- As a clear waterproofing coating on tile finishes for balconies, lobbies, toilets, bathrooms, etc.
- For prevention of glass fragments against shattering.
- For finishing over concrete or synthetic coatings.

## Advantages

- Waterproofing properties
- Easy application: One component
- It produces transparent film, no yellowing
- Highly hydrolysis resistance
- Good Chemical resistance
- Good abrasion resistance
- Slip reduction
- Cost and time saving

## Technical Data

Product Type	QUICSEAL108M	QUICSEAL108G
Odor	odorless	solvent smell
Finishing	Matt	Gloss
Tack Free Time (hrs)		> 4
Working Temperature (°C)		-40 to 100
Light Pedestrian Traffic Time (hrs)		> 24

## Surface Preparation

Surfaces must be sound, clean, dry and free from oil, grime or any contamination and before application of QUICSEAL 108.

Concrete substrate should be levelled and cured for at least 14 days. Laitance, shutter release, curing compound or any substance that may inhibit the adhesion of QUICSEAL 108 must be removed while existing cracks should be repaired with QUICSEAL 304 Epoxy Putty or QUICSEAL 514 Repair Mortar.

NB : Ensure that the substrate is dry before application.

## Application

Apply QUICSEAL 108 evenly by brush, mohair roller, squeegee or non-atomising spray. Where necessary, additional coats can be applied to achieve desired performance.

Avoid over-treating as this will contribute to a glazed effect on the treated surface.

To improve adhesion, a tile primer can be used to prime the tile surface prior to application of QUICSEAL 108.

## Packing & Coverage

	QUICSEAL 108M	QUICSEAL 108G
Pack size:	1, 4 & 10 kg per tin	1, 5 & 10 kg per tin
Approximate coverage:	0.04 ~ 0.2kg/m <sup>2</sup> .	0.06 ~ 0.2kg/m <sup>2</sup>

Note: Consumption of material may vary depending on the types of substrates.

## Storage

The shelf life of QUICSEAL 108 is 12 months when stored unopened in a cool and dry place.

## Cleaning

Clean all brushes and tools with solvent immediately after use.

## Health & Safety

Gloves and facemask should be worn. Any splashes to the skin or eyes should be washed off with clean water. In the event of prolonged irritation, seek medical advice. Use in well ventilated environment.

## Important Notes

The information set forth herein is furnished in good faith and is based on technical data that QUICSEAL considers to be reliable. This information is intended for use by persons having technical skill and at their own discretion and risk. Information contained in this product sheet conforms to the standard detail recommendations and specifications for the installation of QUICSEAL products as of the date of publication of this document. QUICSEAL makes no other warranties and assumes no liability, expressed or implied, as to the architecture, engineering or workmanship of any project. To ensure that you are using the latest, most complete information, contact QUICSEAL

Reference No. 108/101209