



QUICSEAL 651

Product Name

Q - Cleaner

Description

QUICSEAL 651 is a slightly acidic cleaner specially formulated to be used on delicate surfaces. The product is made of a combination of detergents and acids and is excellent for removing concrete film, cement residues and also stubborn stains which are difficult to be cleaned with common detergents. It has been studied to remove haloes due to grouting on porous surfaces. It can be applied and left on the surface for 1 - 2 hours without causing any damage to the grout.

Uses

QUICSEAL 651 can be used to clean all types of surfaces which are resistant to acids. It is excellent for cleaning honed, brushed, aged natural stones, slate, glazed ceramic tiles, terracotta and polished granite.

Technical Data

Appearance	Transparent viscous liquid
Odour	Slightly perfumed
pH (5% solution in water)	4 ~ 4.5
Specific gravity (20°C)	1.07
Biodegradability	90%

Application

For the first washing to remove cement residues and for the cleaning of all unpolished surfaces (except granite) dilute the product from 1 : 4 to 1 : 10 in water. Let it stand for a few minutes and scrub with floor machine or a pad. (Do not apply the pure product on brushed limestone or marble. Rinse thoroughly with clean water.

Note: Do not use the product on polished marble, polished limestone, terrazzo etc.

Caution

It is an acid reaction based product, caustic for eyes and skin. Use gloves, rubber shoes and glasses. Avoid contact with eyes and skin. In case of contact with eyes wash with plenty of water and call for a doctor. Keep out of children's reach.

Packaging

QUICSEAL 651 is supplied in 1, 5 and 10 litre tins.

Shelf life

24 ~ 36 months in original sealed packing kept in cool and dry place.

Important Notes

The information set forth herein is furnished free of charge in good faith and is based on technical data that QUICSEAL considers to be reliable. This information is intended for used by persons having technical skill and at their own discretion and risk. Information contained in this product sheet conforms to the standard detail recommendations and specifications for the installation of QUICSEAL products as of the date of publication of this document. QUICSEAL makes no other warranties and assumes no liability, expressed or implied, as to the architecture, engineering or workmanship of any project. To ensure that you are using the latest, most complete information, please contact QUICSEAL

Reference No. QS651/220310