



QUICSEAL 661

Product Name

Q – Strip PN

Description

QUICSEAL 661 is a single-component neutral-activated stripper with a high capacity to remove even many layered coatings

Uses

It is particularly indicated for building supports and monuments in stone, brick cement, cast iron and other metals. It is a medium viscosity product applicable on vertical surfaces as well. It removes the majority of writing and marks provoked by spray paint and nitrocellulose, synthetic, oil, polyester and polyurethane based paints.

Advantages

- Easy to use - Can be used directly from the can.
- Viscous - adheres to vertical and undercut surfaces.
- Economical - Consumption notably lower than traditional strippers.

Application

The surface to be stripped must be cleaned, degreased, and dry. The temperature should not be lower than 18° C. Lower temperatures may slow down or stop the stripping effect.

Using appropriate brushes or standard equipment furnished with a non-atomising sprayer, apply QUICSEAL 661 to the surface to be stripped in a uniform layer.

Wait for complete penetration (approximately 20 minutes to three hours). Agitating the applied product with a soft brush will accelerate the removal of the coating.

Allow for chemical reaction to occur. The colour of the coating to be removed will disappear.

REMOVAL: Remove the unreacted stripper and the detached coating with a blade. The stripped surfaces can then be rinsed with a spray of water.

Do not apply the stripper on surfaces exposed to the sun. If necessary repeat the application of the stripper in the areas it is needed.

Packing

QUICSEAL 661 is supplied in 1 litre & 5 litre container.

Shelf life

12 months when kept in a cool and ventilated place at temperature between 0 and 30°C in the original packaging. If the material has been stored for longer than its recommended shelf life, it might still be suitable, but this has to be determined beforehand by performing quality checks on its application-related properties

Health & Safety

Gloves, goggles and protective clothing should be worn. Avoid contact with the eyes and skin. In case of contact with eyes, immediately flush the eyes with water and consult a doctor.

Any splashes to the skin or eyes should be washed off with clean water. In the event of prolonged irritation, seek medical advice. Areas of use should be well ventilated.

Do not breathe in the vapours. In the case of fire or explosion do not inhale the fumes. The product is hazardous for inhalation and ingestion and is toxic for aquatic organisms, may provoke negative effects over the long term for the aquatic environment. Keep the container well closed when not in use. Dispose material and its container as dangerous waste.

Keep out of the reach of children

Important Notes

The information set forth herein is furnished free of charge in good faith and is based on technical data that QUICSEAL considers to be reliable. This information is intended for use by persons having technical skill and at their own discretion and risk. Information contained in this product sheet conforms to the standard detail recommendations and specifications for the installation of QUICSEAL products as of the date of publication of this document. QUICSEAL makes no other warranties and assumes no liability, expressed or implied, as to the architecture, engineering or workmanship of any project. To ensure that you are using the latest, most complete information, please contact QUICSEAL

Reference No. QS661/091212

QUICSEAL CONSTRUCTION CHEMICALS PTE LTD

QUICSEAL – the professional's choice of quality products and systems for building construction