



# QUICSEAL 535

## Product Name

Paver-Top N

## Description

QUICSEAL 535 Paver-Top N is a single component, quality controlled, factory blended, ready to use monolithic surface hardening compound. It consists of a special blend of hardwearing aggregates, high performance workability admixtures to produce a material which is applied as a dry shake over freshly floated concrete or floor screed.

## Typical Uses

QUICSEAL 535 provides a highly abrasion resistant surface to concrete floor by the dry shake method. It is ideal for use in all industrial areas subjected to the heaviest traffic, e.g. carparks, ramps, workshops, loading bays, factory floors, production areas, etc.

## Advantages

- Pre-packed - easy and economical to apply
- Forms monolithic bond with base concrete.
- Provides a hard, abrasion resistant surface.
- Resistant to oil and grease
- Non-metallic - QUICSEAL 535 provides a non-slip, non-rusting surface.

## Instructions for Use

The base concrete should be placed and compacted in accordance with good concrete practice.

## Application

QUICSEAL 535 is applied at different application rate to meet the demands for different types of usage.

The sprinkling is broadcast in two applications, perpendicular to each other to achieve a more uniform coverage.

For the first broadcast, sprinkle 2/3 of the required quantity QUICSEAL 535 onto a freshly spread and floated concrete slab surface (foot pressure results in 3-5mm indentation) after the water sheen has disappeared.

Allow sufficient time for the QUICSEAL 535 to be moistened by the water from the base concrete or color tone to turn darker before floating.

QUICSEAL 535 shall be floated by hand or mechanical power floating to embed the hardener onto the surface of the concrete.

Allow 30-50 minutes time interval before carrying out the second broadcast. Broadcast the remaining QUICSEAL 535 at right angle to the first and further power troweled until a hard, wear resistant surface is obtained.

Further troweling is recommended using a power float to achieve the desired finish.

**QUICSEAL CONSTRUCTION CHEMICALS PTE LTD**

*QUICSEAL – the professional's choice of quality products and systems for building construction*

## Curing

Proper curing and sealing is essential to achieve optimum performance of the floor finish. Upon completion of application of QUICSEAL PAVER-TOP, the floor should be treated with QUICSEAL 507 CURE-SHIELD WB curing compound. Other curing methods such as polyethylene sheets are also acceptable.

Apply CURE-SHIELD WB by spray over the freshly laid surface once the surface does not leave any foot imprint. If spray equipment is not available, apply with a soft brush when the surface is hard enough.

## Packing & Coverage

QUICSEAL 535 is supplied in sealed 25 kg bags.

Coverage:

Intended traffic use	Application rate kg/m <sup>2</sup>	Coverage per bag
Light traffic	3.0 - 3.5	7 - 8m <sup>2</sup>
Moderate traffic	4.5 - 5.0	5 - 5.5m <sup>2</sup>
Heavy traffic	7.0 – 7.5	3 - 3.5m <sup>2</sup>

## Technical Data

Color	Natural, Cool Grey, Leaf Green
Abrasion resistance (Moh Hardness)	7
Compressive strength	60 N/mm <sup>2</sup>

## Storage

The shelf life of QUICSEAL 535 is 12 months when stored unopened, and kept in a cool and dry place.

## Health & Safety

Gloves goggles and dust mask should be worn. Any splashes to the skin or eyes should be washed off with clean water. In the event of prolonged irritation, seek medical advice. Powder products should be handled to minimize dust formation.

## Important Notes

The information set forth herein is furnished free of charge in good faith and is based on technical data that QUICSEAL considers to be reliable. This information is intended for used by persons having technical skill and at their own discretion and risk. Information contained in this product sheet conforms to the standard detail recommendations and specifications for the installation of QUICSEAL products as of the date of publication of this document. QUICSEAL makes no other warranties and assumes no liability, expressed or implied, as to the architecture, engineering or workmanship of any project. To ensure that you are using the latest, most complete information, please contact QUICSEAL.

Reference No. 535/020216

**QUICSEAL CONSTRUCTION CHEMICALS PTE LTD**

*QUICSEAL – the professional's choice of quality products and systems for building construction*