



**SAFETY DATA SHEET
QUICSEAL 107
PENETRATING SEALER**

1. INFORMATION OF THE SUBSTANCE/COMPOUND AND THE SUPPLIER

Product Name: QUICSEAL 107 – Penetrating Sealer
Product Use: Concrete sealer

Details of the supplier:

*QUICSEAL CONSTRUCTION CHEMICALS PTE LTD
No. 7 Eunos Avenue 8A
Eunos Industrial Estate
Singapore 409460*

Emergency Contact No.: (65) 6742 4466

2. HAZARDS IDENTIFICATION

Flammable liquid – Category 3
Acute dermal toxicity – Category 4
Acute inhalation toxicity – Category 4
Skin irritation – Category 2

GHS LABEL ELEMENTS

Symbol(s):



Signal Word

Danger

Hazard statements:

H226: Flammable liquid and vapour
H312: Harmful in contact with skin
H315: Causes skin irritation
H332: Harmful if inhaled

QUICSEAL CONSTRUCTION CHEMICALS PTE LTD

No. 7 Eunos Avenue 8A Eunos Industrial Estate Singapore 409460 Tel: (65) 6742 4466 Fax: (65) 6741 4666

Website: www.quicseal.com Co.Reg. No.: 198201286W



165581CC1-2014-AQ-GER-DAMK



165582CC1-2014-AE-GER-DAMK

Precautionary statements:Prevention

P210: Keep away from heat/sparks/open flames/hot surfaces. No smoking

P233: Keep container tightly closed.

P240: Ground/bond container and receiving equipment.

P241: Use explosion-proof electrical/ventilating/lighting equipment.

P242: Use only non-sparking tools.

P243: Take precautionary measures against static discharge.

P261: Avoid breathing vapours.

P264: Wash hands and forearms thoroughly after handling.

P270: Do not eat, drink or smoke when using this product.

P271: Use in well-ventilated areas.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

Response

P301+P310: IF SWALLOWED: Immediately call a poison center or doctor. Do NOT induce vomiting.

P303+P361+P353: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P304+P340: IF INHALED: Remove victim to fresh air and keep at rest in apposition comfortable to breathing.

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center or doctor/physician.

P308+P313: If exposed or concerned: Get medical advice/attention.

P312: Call a POISON CENTER or doctor/physician if you feel unwell.

P332+P313: If skin irritation occurs: Get medical advice/attention.

P337+P313: If eye irritation persists: Get medical advice/attention.

P363: Wash contaminated clothing before reuse.

P370+P378: In case of fire: Use appropriate extinction.

Storage

P403+P235: Store in a well ventilated place. Keep cool.

P405: Store locked up.

Disposal

P501: Dispose of contents/container in accordance with local/national regulations.

3. COMPOSITION / INFORMATION ON INGREDIENTS

This product contains the following components classified as hazardous:

COMPONENTS	CAS No.	EINECS No.	Index No.	Percentage
Xylene (1,4-Dimethylbenzene, p-Xylene, para-Xylene, p-Xylol)	1330-20-7	202-422-2	601-022-00-9	75 – 95%

QUICSEAL CONSTRUCTION CHEMICALS PTE LTD

No. 7 Eunos Avenue 8A Eunos Industrial Estate Singapore 409460 Tel: (65) 6742 4466 Fax: (65) 6741 4666

Website: www.quicseal.com Co.Reg. No.: 198201286W



4. FIRST-AID MEASURES

General information

Take person to a safe place. Observe self-protection for first aid. Always seek medical advice in the event of contact with this substance.

Inhalation

Keep the patient calm. If unconscious place in stable sideways position. Protect against loss of body heat. If breathing stops, administer artificial respiration. Seek medical advice immediately and clearly identify substance.

Skin contact

Remove contaminated clothes at once. Wash off with plenty of water or water and soap immediately for 10-15 minutes. In serious cases, use emergency shower immediately. Seek medical advice immediately and clearly identify substance.

Eye contact

Rinse immediately with plenty of water for 10-15 minutes. Keep eyelids well open to rinse the whole eye surface and eyelids with water. Seek medical advice immediately and clearly identify substance. Continue to bathe eyes during transport to medical practitioner.

Ingestion

If conscious, give several small portions of water to drink. Do not induce vomiting. Seek medical advice immediately and clearly identify substance.

Notes to physician

Treat patient symptomatically (decontamination, vital functions).

5. FIRE-FIGHTING MEASURES

General Fire Hazards

This product is classified as a FLAMMABLE LIQUID. See Section 9 for Flammability Properties.

Vapors may be ignited rapidly when exposed to heat, spark, open flame or other source of ignition. When mixed with air and exposed to an ignition source, flammable vapors can burn in the open or explode in confined spaces. Being heavier than air, vapors may travel long distances to an ignition source and flash back. Runoff to sewer may cause fire or explosion hazard.

Suitable Fire-extinguishing Media

SMALL FIRES: Any extinguisher suitable for Class B fires, dry chemical, CO₂, water spray, fire fighting foam, and other gaseous agents.

LARGE FIRES: Water spray, fog or fire fighting foam. Water may be ineffective for fighting the fire, but may be used to cool fire-exposed containers.

Fire-fighting Equipment / Instructions

Small fires in the incipient (beginning) stage may typically be extinguished using handheld portable fire extinguishers and other fire fighting equipment. Fire-fighting activities that may result in potential exposure to high heat, smoke or toxic by-products of combustion should require NIOSH/MSHA- approved pressure-demand self-contained breathing apparatus with full facepiece and full protective clothing. Isolate area around container involved in fire. Cool tanks, shells, and containers exposed to fire and excessive heat with water. For massive fires the use of unmanned

QUICSEAL CONSTRUCTION CHEMICALS PTE LTD

No. 7 Eunos Avenue 8A Eunos Industrial Estate Singapore 409460 Tel: (65) 6742 4466 Fax: (65) 6741 4666

Website: www.quicseal.com Co.Reg. No.: 198201286W



hose holders or monitor nozzles may be advantageous to further minimize personnel exposure. Major fires may require withdrawal, allowing the tank to burn. Large storage tank fires typically require specially trained personnel and equipment to extinguish the fire, often including the need for properly applied fire fighting foam.

Hazardous Combustion Products

Carbon monoxide, carbon dioxide and non-combusted hydrocarbons (smoke).

Further information

Dispose of fire debris and contaminated extinguishing water in accordance with official regulations.

6. ACCIDENTAL RELEASE MEASURES

Emergency Measures

Evacuate nonessential personnel and remove or secure all ignition sources. Consider wind direction; stay upwind and uphill, if possible. Evaluate the direction of product travel, diking, sewers, etc. to confirm spill areas. Spills may infiltrate subsurface soil and groundwater; professional assistance may be necessary to determine the extent of subsurface impact.

Personal Precautions and Protective equipment

Response and clean-up crews must be properly trained and must utilize proper protective equipment (see Section 8).

Environmental Precautions

Protect bodies of water by diking, absorbents, or absorbent boom, if possible. Do not flush down sewer or drainage systems, unless system is designed and permitted to handle such material. The use of fire fighting foam may be useful in certain situations to reduce vapors. The proper use of water spray may effectively disperse product vapors or the liquid itself, preventing contact with ignition sources or areas/equipment that require protection.

Methods and materials for containment and cleaning up

Carefully contain and stop the source of the spill, if safe to do so.

Take up with sand or other oil absorbing materials. Carefully shovel, scoop or sweep up into a waste container for reclamation or disposal. Caution, flammable vapors may accumulate in closed containers.

7. HANDLING AND STORAGE

Precautions for Safe Handling

Handle as a combustible liquid. Keep away from heat, sparks, excessive temperatures and open flame! No smoking or open flame in storage, use or handling areas. Bond and ground containers during product transfer to reduce the possibility of static-initiated fire or explosion.

Special slow load procedures for "switch loading" must be followed to avoid the static ignition hazard that can exist when higher flash point material (such as fuel oil) is loaded into tanks previously containing low flash point products (such as this product) - see API Publication 2003, "Protection Against Ignitions Arising Out Of Static, Lightning and Stray Currents."

QUICSEAL CONSTRUCTION CHEMICALS PTE LTD

No. 7 Eunos Avenue 8A Eunos Industrial Estate Singapore 409460 Tel: (65) 6742 4466 Fax: (65) 6741 4666

Website: www.quicseal.com Co.Reg. No.: 198201286W



Conditions for safe storage, including any incompatibilities

Keep away from flame, sparks, excessive temperatures and open flame. Use approved vented containers. Keep containers closed and clearly labelled. Empty product containers or vessels may contain explosive vapors. Do not pressurize, cut, heat, weld or expose such containers to sources of ignition.

Store in a well-ventilated area. Avoid storage near incompatible materials. Keep away from strong oxidizers.

8. EXPOSURE CONTROLS AND PERSONAL PROTECTION**Control Parameters / Occupational Exposure Limits**

For component: Xylene, CAS No.: 1330-20-7

Singapore Permissible Exposure Level (PEL), short term: 150 ppm / 651 mg/m³

Singapore Permissible Exposure Level (PEL), long term: 100 ppm / 434 mg/m³

Engineering Measures

Use adequate ventilation to keep vapor concentrations of this product below occupational exposure and flammability limits, particularly in confined spaces.

Personal Protective Equipment:Hand Protection

Gloves constructed of nitrile, neoprene, or PVC are recommended.

The following should be considered when choosing work glove material: degradation, breakage times and permeation. Work glove resistance to preparations should be checked before use, as it can be unpredictable. Gloves' limit depends on the duration of exposure.

Eye Protection

Safety glasses or goggles are recommended where there is a possibility of splashing or spraying.

Skin Protection

Chemical protective clothing such as of E.I. DuPont TyChem®, Saranex® or equivalent recommended based on degree of exposure. Note: The resistance of specific material may vary from product to product as well as with degree of exposure. Consult manufacturer specifications for further information.

Respiratory Protection

A NIOSH/MSHA-approved air-purifying respirator with organic vapor cartridges or canister may be permissible under certain circumstances where airborne concentrations are or may be expected to exceed exposure limits or for odor or irritation. Protection provided by air-purifying respirators is limited.

Use a positive pressure, air-supplied respirator if there is a potential for uncontrolled release, exposure levels are not known, in oxygen-deficient atmospheres, or any other circumstance where an air-purifying respirator may not provide adequate protection.

QUICSEAL CONSTRUCTION CHEMICALS PTE LTD

No. 7 Eunos Avenue 8A Eunos Industrial Estate Singapore 409460 Tel: (65) 6742 4466 Fax: (65) 6741 4666

Website: www.quicseal.com Co.Reg. No.: 198201286W



9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state:	Liquid
Color:	Very light straw to clear liquid
Odour:	Specific odour
Flash Point:	40°C
Initial boiling point and boiling range:	144°C (o-), 139°C (m-), 138°C (p-)
Freezing / Melting point:	-25°C (o-), -48°C (m-), 13°C (p-)
Autoignition temperature:	463°C (o-), 527°C (m-), 527°C (p-)
Flammability Limits:	0.9-6.7 vol% (o-), 1.1-7.0 vol% (m-), 1.1-7.0 vol% (p-)
Vapor pressure (20°C):	0.7 kPa (o-), 0.8 kPa (m-), 0.9 kPa (p-)
Vapor density:	3.66 (o-, m-, p-) (calculated value)
Water Solubility (25°C):	178mg/L (o-), 162mg/L (m-), 198mg/L (p-),
Solubility in other solvents:	Mixing with ethanol, ethyl ether and acetone (o-) Soluble in most organic solvent (m-) Mixing with alcohol, ether, other, many organic solvents (p-)
Partition coefficient:	n-octanol/water: log P _{ow} = 3.12 (o-), 3.2 (m-), 3.15 (p-)
Specific Gravity:	Approx. 1.0

10. STABILITY AND REACTIVITY

Chemical stability

The product is flammable. The liquid and vapour is readily combustible.

Possibility of hazardous reactions

This product reacts with strong oxidizing agents.

Conditions to avoid

Avoid high temperatures, open flames, sparks, welding, smoking and other ignition sources.

Incompatible materials

Keep away from strong oxidizers.

Hazardous decomposition products

Carbon monoxide, carbon dioxide and non-combusted hydrocarbons (smoke).

11. TOXICOLOGICAL INFORMATION

This product has not been tested and all the toxicological statements have been derived from the respective components' available toxicity information.

Acute toxicity

Experimental/calculated data:

LD50, oral: > 5,000 mg/kg (the product is not toxic/harmful if swallowed.)

LD50, dermal: > 5,000 mg/kg (the product is not toxic/harmful in contact with skin)

LC50, inhalation: > 20 mg/L (the product is not toxic/harmful if inhaled)

QUICSEAL CONSTRUCTION CHEMICALS PTE LTD

No. 7 Eunos Avenue 8A Eunos Industrial Estate Singapore 409460 Tel: (65) 6742 4466 Fax: (65) 6741 4666

Website: www.quicseal.com Co.Reg. No.: 198201286W



Skin and Eye Irritation

The product contains the following components with their respective skin and eye corrosion/irritation classification:

COMPONENTS	CAS No.	Animal skin test result	Animal eye test result
Xylene	1330-20-7	Moderate Irritant (Skin Irritant Category 2)	Moderate Irritant (Eye Irritant Category 2)

Respiratory / Skin sensitization

The product is not expected to cause respiratory or skin sensitization.

Germ cell mutagenicity

Based on the negative data on human multi-generation epidemiological studies and somatic cell mutagenicity tests in vivo (micronucleus/chromosome tests) and the absence of data on heritable mutagenicity tests, germ cell mutagenicity tests in vivo and germ cell genotoxicity tests in vivo, described in CERI-NITE Hazard Assessment No.62 (2004), CaPSAR (1993), IARC (1999) and NTP DB (Access on December 2005).

Carcinogenicity / Developmental toxicity

The product has no known carcinogenic effect and is not expected to cause developmental toxicity.

Reproductive toxicity

Based on the evidence of weight reduction and hydrocephalus in foetuses at dosing levels not toxic to parent animals in mouse developmental toxicity tests, described in CERI-NITE Hazard Assessment (No. 62, 2004), EHC 190 (1997) and IRIS (2003), this product may damage fertility or the unborn child (Reproductive toxicity Category 1B)

Specific target organ toxicity - single exposure

Based on the human evidence including "throat irritation, severe pulmonary congestion, alveolar hemorrhage, pulmonary edema, congestion accompanying hepatomegaly, centrilobular vacuolation of hepatocytes, nerve cell damage associated with dot hemorrhage, swelling and disappearance of Nissl bodies, limb cyanosis, a transient increase in serum transaminase activity, an increase in the blood level of urea, a decrease in endogenous creatinine clearance in the urine, liver damage, severe kidney damage, amnesia, coma" (CERI-NITE Hazard Assessment No.62, 2004) and "pulmonary congestion, pulmonary edema, focal alveolar hemorrhage" (MOE Risk Assessment Vol.1, 2002) and the evidence from animal studies including "strong narcotic effect (EHC 190, 1997). The basis for the classification includes data on xylene with unknown composition or containing other substances (ethyl benzene, toluene, etc.).

The product causes damage to respiratory, liver, central nervous system, kidney May cause drowsiness or dizziness (Specific target organ toxicity - Single exposure Category 1(respiratory, liver, central nervous system, kidney), 3 (drowsiness and dizziness))

Specific target organ toxicity - repeated exposure

Based on the human evidence including "eye/nose irritation, thirst" (DFGOT Vol. 15, 2001) and "chronic headache, chest pain, abnormal electroencephalogram, dyspnea, cyanosis of the hands, fever, a decrease in WBC count, discomfort, impairment of pulmonary function, a decrease in working capacity, physical/mental disorders" (CERI-NITE Hazard Assessment No.62, 2004). The basis for the classification includes data on xylene with unknown composition or containing other substances (ethyl benzene, toluene, etc.).

QUICSEAL CONSTRUCTION CHEMICALS PTE LTD

No. 7 Eunos Avenue 8A Eunos Industrial Estate Singapore 409460 Tel: (65) 6742 4466 Fax: (65) 6741 4666

Website: www.quicseal.com Co.Reg. No.: 198201286W



The product causes damage to respiratory, nervous system through prolonged or repeated exposure (Specific target organ toxicity - Repeated exposure Category 1 (respiratory, nervous system)).

Aspiration hazard

Based on the description in ICSC(J) (2002) regarding o-xylene, m-xylene and p-xylene: "May cause aspiration and chemical pneumonia if swallowed".

This product may be harmful if swallowed and enters airways (Aspiration hazard Category 2)

12. ECOLOGICAL INFORMATION

The following ecological assessment is based on the available ecotoxicity information of the product's components.

Acute toxicity to the aquatic environment

Toxicity to fish: LC50 (96h): 3.3 mg/l, Rainbow trout (OECD Guideline 203, static)

This product is toxic to aquatic life (Acute toxicity to the aquatic environment Category 2)

13. DISPOSAL CONSIDERATIONS**Description of waste residues and information on their safe handling & methods of disposal**

Dispose of the product through licensed hazardous waste collectors under Singapore regulations. Provide the hazardous waste collector the sufficient information on the various hazards of this product.

Disposal of any contaminated packaging

Dried material can be disposed off in authorized landfill site in accordance to national regulations. Container should be recycled after cleaning or dispose of the container through licensed hazardous waste collectors under Singapore regulations. Provide the hazardous waste collector the sufficient information on the various hazards of this product in this container.

14. TRANSPORT INFORMATION**Land Transport (ADG):**

Shipping Name: XYLENES

UN #: 1307

Hazard Class: 3

Letter: F

Packing Group: II

Label:

**Air Transport (IATA):**

Shipping Name: XYLENES

UN #: 1307

Class: 3

Letter: F

Packaging group: II

Label:

**QUICSEAL CONSTRUCTION CHEMICALS PTE LTD**

No. 7 Eunos Avenue 8A Eunos Industrial Estate Singapore 409460 Tel: (65) 6742 4466 Fax: (65) 6741 4666

Website: www.quicseal.com Co.Reg. No.: 198201286W



Sea transport (IMDG):

Shipping Name: XYLENES

UN #: 1307

Class: 3

Letter: F

Packaging group: II

EmS Number: F-E S-D

Marine pollutant: No

Label:

**15. REGULATORY INFORMATION****Applicable National Regulations**

This product is subject to the requirements in the following acts/regulations:

Workplace Safety and Health Act & Workplace Safety and Health (General Provisions) Regulations
Environmental Protection and Management Act and Environmental Protection and Management
Maritime and Port Authority of Singapore (Dangerous Goods, Petroleum and Explosives)

International Regulations

This product is classified as hazardous pursuant to the provision set forth in Directives 67/548/EEC and 1999/45/EC and/or EC Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of EC Regulation 1907/2006 and subsequent amendments.

16. OTHER INFORMATION

The information and data contained herein are believed to be accurate and reliable; however, it is the user's responsibility to determine suitability of use. Since QUICSEAL Construction Chemicals Pte. Ltd. cannot know all of the uses to which its products may be put or the conditions of use; it makes no warranties concerning the fitness or suitability of its products for a particular use of purpose.

QUICSEAL CONSTRUCTION CHEMICALS PTE LTD

No. 7 Eunos Avenue 8A Eunos Industrial Estate Singapore 409460 Tel: (65) 6742 4466 Fax: (65) 6741 4666

Website: www.quicseal.com Co.Reg. No.: 198201286W

