



**SAFETY DATA SHEET  
QUICSEAL 135 – PART A  
EPOXY PRIMER, SOLVENT-FREE**

**1. INFORMATION OF THE SUBSTANCE/COMPOUND AND THE SUPPLIER**

Product Name: QUICSEAL 135 – Epoxy Primer, Solvent-free (Part A)  
Product Use: Primer for epoxy flooring system and polyurethane coating

Details of the supplier:

*QUICSEAL CONSTRUCTION CHEMICALS PTE LTD  
No. 7 Eunos Avenue 8A  
Eunos Industrial Estate  
Singapore 409460*

Emergency Contact No.: (65) 6742 4466

**2. HAZARDS IDENTIFICATION**

**GHS Classification:**

Skin irritation – Category 2  
Eye irritation – Category 2  
Skin sensitization – Category 1  
Chronic aquatic toxicity – Category 2

**GHS LABEL ELEMENTS**

**Symbol(s):**



**Signal Word**

Warning

**Hazard Statements:**

H315: Causes skin irritation  
H319: Causes serious eye irritation  
H317: May cause an allergic skin reaction  
H411: Toxic to aquatic life with long lasting effects.

**Precautionary Statements:**

Prevention

P261: Avoid breathing fume/mist/vapours/spray.  
P264: Wash hands and forearms thoroughly after handling.  
P272: Contaminated work clothing should not be allowed out of the workplace.  
P273: Avoid release to the environment.  
P280: Wear protective gloves/protective clothing/eye protection/face protection.

**QUICSEAL CONSTRUCTION CHEMICALS PTE LTD**

No. 7 Eunos Avenue 8A Eunos Industrial Estate Singapore 409460 Tel: (65) 6742 4466 Fax: (65) 6741 4666

Website: [www.quicseal.com](http://www.quicseal.com) Co.Reg. No.: 198201286W



Response

P302+P352: IF ON SKIN: Wash with plenty of soap and water.

P333+P313: If skin irritation or rash occurs: Get medical advice/attention.

P363: Take off contaminated clothing and wash before reuse.

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center or doctor/physician.

P337+P313: If eye irritation persists: Get medical advice/attention.

P391: Collect spillage.

Disposal

P501: Dispose of contents/container in accordance with local/national regulations.

**3. COMPOSITION / INFORMATION ON INGREDIENTS**

This product contains the following components classified as hazardous:

COMPONENTS	CAS No.	EINECS No.	Index No.	Percentage
Liquid epoxy resin	<i>Undisclosed / Proprietary</i>	<i>Undisclosed / Proprietary</i>	<i>Undisclosed / Proprietary</i>	<i>Undisclosed / Proprietary</i>

**4. FIRST-AID MEASURES****General information**

Take person to a safe place. Observe self-protection for first aid. Always seek medical advice in the event of contact with this substance.

**Inhalation**

Keep the patient calm. If unconscious place in stable sideways position. Protect against loss of body heat. If breathing stops, administer artificial respiration. Seek medical advice immediately and clearly identify substance.

**Skin contact**

Remove contaminated clothes at once. Wash off with plenty of water or water and soap immediately for 10-15 minutes. In serious cases, use emergency shower immediately. Seek medical advice immediately and clearly identify substance.

**Eye contact**

Rinse immediately with plenty of water for 10-15 minutes. Keep eyelids well open to rinse the whole eye surface and eyelids with water. Seek medical advice immediately and clearly identify substance. Continue to bathe eyes during transport to medical practitioner.

**Ingestion**

If conscious, give several small portions of water to drink. Do not induce vomiting. Seek medical advice immediately and clearly identify substance.

**Notes to physician**

Treat patient symptomatically (decontamination, vital functions).

**QUICSEAL CONSTRUCTION CHEMICALS PTE LTD**

No. 7 Eunos Avenue 8A Eunos Industrial Estate Singapore 409460 Tel: (65) 6742 4466 Fax: (65) 6741 4666

Website: [www.quicseal.com](http://www.quicseal.com) Co.Reg. No.: 198201286W



## 5. FIRE-FIGHTING MEASURES

### General Fire Hazards

The product is non-flammable (water-borne system). If material is involved in fire, do not breathe fumes.

### Suitable Fire-extinguishing Media

Use the appropriate fire extinguishing media for surrounding fire (water, foam, dry powder, CO<sub>2</sub>)

### Hazardous Combustion Products

Carbon monoxide, carbon dioxide and non-combusted hydrocarbons (smoke).

### Advice for fire-fighters

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Do not use a solid water stream as it may scatter and spread fire.

### Further information

Dispose of fire debris and contaminated extinguishing water in accordance with official regulations.

## 6. ACCIDENTAL RELEASE MEASURES

### Emergency Measures

Emergency and non-emergency responders should use personal protective equipment. Avoid contact with skin and eyes. Do not breathe vapours/aerosol.

### Personal Precautions and Protective equipment

Response and clean-up crews must be properly trained and must utilize proper protective equipment (see Section 8).

### Environmental Precautions

Protect bodies of water by diking, absorbents, or absorbent boom, if possible. Do not flush down sewer or drainage systems, unless system is designed and permitted to handle such material.

### Methods and materials for containment and cleaning up

Carefully contain and stop the source of the spill, if safe to do so.

Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).

Keep in suitable and closed containers for disposal. Clean contaminated surface thoroughly.

## 7. HANDLING AND STORAGE

### Precautions for Safe Handling

Avoid all personal contact, including inhalation. Wear protective clothing when risk of exposure occurs. Do not allow clothing to be wet with product. Use in a well-ventilated area. Avoid contact with moisture and incompatible materials. When handling, do not eat, drink or smoke. Keep containers securely sealed when not in use and avoid physical damage to containers. Always wash hands with soap and water after handling. Work clothes should be laundered separately. Launder contaminated clothing before re-use. Observe manufacturer's storing and handling recommendations. Atmosphere should be regularly checked against established exposure standards to ensure safe working conditions are maintained.

## QUICSEAL CONSTRUCTION CHEMICALS PTE LTD

No. 7 Eunos Avenue 8A Eunos Industrial Estate Singapore 409460 Tel: (65) 6742 4466 Fax: (65) 6741 4666

Website: [www.quicseal.com](http://www.quicseal.com) Co.Reg. No.: 198201286W



**Conditions for safe storage, including any incompatibilities**

Store in original container (polyethylene or polypropylene container) as recommended by the manufacturer. Check all containers are clearly-labelled and free from leaks. Keep containers securely sealed. Store in a cool, dry, well-ventilated area. Store away from incompatible materials (oxidizing agents, strong acids, bases and amines) and foodstuff containers. Protect containers against physical damage and check regularly for leaks.

**8. EXPOSURE CONTROLS AND PERSONAL PROTECTION****Control parameters / Occupational Exposure Limits**

This product contains no component that has relevant occupational exposure limits.

**Appropriate engineering control measures**

There are no specific engineering control measures necessary for this product. However, it is of good practice to use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels of fumes.

**Personal Protective Equipment**Hand Protection

Protective gloves complying with EN 374. Gloves made of nitrile.  
Break through time: > 4 h.

Eye Protection

Safety glasses with side-shields conforming to EN 166. Eye wash bottle with pure water.

Skin / Body Protection

Long sleeved clothing. Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Respiratory Protection

No personal respiratory protective equipment normally required. Breathing apparatus needed only when aerosol or mist is formed. Respirator with A/P2 filter.

**9. PHYSICAL AND CHEMICAL PROPERTIES**

Physical state:	Pale yellow liquid
Odour:	None
Flash Point:	121°C
Boiling point:	Not available
Freezing point:	< -5°C
Autoignition temperature:	Not available
Flammability Limits:	Not available
Vapor pressure (20°C):	Not available
Vapor density:	Not available
Water Solubility (25°C):	< 1% w/w
Specific Gravity:	1.11 – 1.16
pH:	Not applicable

**QUICSEAL CONSTRUCTION CHEMICALS PTE LTD**

No. 7 Eunos Avenue 8A Eunos Industrial Estate Singapore 409460 Tel: (65) 6742 4466 Fax: (65) 6741 4666

Website: [www.quicseal.com](http://www.quicseal.com) Co.Reg. No.: 198201286W



## 10. STABILITY AND REACTIVITY

### Chemical stability

The product is stable at normal conditions. No decomposition is expected the product is stored and applied as directed.

### Possibility of hazardous reactions

No hazardous reactions are expected under normal conditions of handling and storage. Keep away from oxidising agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

### Conditions to avoid

Avoid temperatures above 60°C, direct sunlight and contact with sources of heat. Burning produces obnoxious and toxic fumes.

### Incompatible materials

Oxidising agents, strongly alkaline and strongly acid materials.

### Hazardous decomposition products

None under normal use. Carbon monoxide, carbon dioxide and non-combusted hydrocarbons (smoke) may be liberated when product is involved in fire.

## 11. TOXICOLOGICAL INFORMATION

This product has not been tested and all the toxicological statements have been derived from the respective components' available toxicity information.

### Acute toxicity

Experimental/calculated data:

LD50, oral: > 5,000 mg/kg (the product is non-harmful/non-toxic if ingested)

LD50, dermal: > 5,000 mg/kg (the product is non-harmful/non-toxic in contact with skin)

LC50, inhalation: > 20 mg/L (the product is non-harmful/non-toxic if inhaled)

### Skin and Eye Irritation

This product may cause skin and eye irritation. (Skin and Eye Irritant - Category 2)

### Respiratory / Skin sensitization

The product's components may cause an allergic skin reaction. This product is not expected to cause allergy or asthma symptoms or breathing difficulties if accidentally inhaled.

### Germ cell mutagenicity / Carcinogenicity / Reproductive toxicity / Developmental toxicity

Based on the assessment of available information, the product is: not mutagenic in bacteria; has no known carcinogenic effect; and not expected to cause reproductive and developmental toxicity.

### Specific target organ toxicity (single and repeated exposure)

Based on the available information, there is no specific target organ toxicity expected after a single or repeated exposure to the product.

## QUICSEAL CONSTRUCTION CHEMICALS PTE LTD

No. 7 Eunos Avenue 8A Eunos Industrial Estate Singapore 409460 Tel: (65) 6742 4466 Fax: (65) 6741 4666

Website: [www.quicseal.com](http://www.quicseal.com) Co.Reg. No.: 198201286W



## 12. ECOLOGICAL INFORMATION

The following ecological assessment is based on the available ecotoxicity information of the product's components.

### Chronic toxicity to the aquatic environment

The product's major components are classified as Category 2 chronic aquatic toxicants. By estimation this product is considered toxic to aquatic life with long lasting effects (Chronic toxicity to the aquatic environment Category 2)

## 13. DISPOSAL CONSIDERATIONS

### Description of waste residues and information on their safe handling & methods of disposal

Dispose of the product through licensed hazardous waste collectors under Singapore regulations. Provide the hazardous waste collector the sufficient information on the various hazards of this product.

### Disposal of any contaminated packaging

Dried material can be disposed off in authorized landfill site in accordance to national regulations. Container should be recycled after cleaning or dispose of the container through licensed hazardous waste collectors under Singapore regulations. Provide the hazardous waste collector the sufficient information on the various hazards of this product in this container.

## 14. TRANSPORT INFORMATION

### Land Transport (ADR):

Proper Shipping Name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S., MIXTURE (contains epoxy resin, liquid)

UN Number: 3082  
Hazard Class: 9  
Packing Group: III

### Air Transport (IATA):

Proper Shipping Name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S., MIXTURE (contains epoxy resin, liquid)

UN Number: 3082  
Hazard Class: 9  
Packing Group: III  
Packing instructions: Passenger aircraft: 914 (450 L)  
Passenger & cargo aircraft: Y914 (30 kg G)  
Cargo aircraft: 914 (450 L)

### Sea transport (IMDG):

Proper Shipping Name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S., MIXTURE (contains epoxy resin, liquid)

UN Number: 3082  
Hazard Class: 9  
Packing Group: III  
EmS Number: F-A S-F  
Marine pollutant: Yes  
Special provisions: 179 274 335 909

## QUICSEAL CONSTRUCTION CHEMICALS PTE LTD

No. 7 Eunos Avenue 8A Eunos Industrial Estate Singapore 409460 Tel: (65) 6742 4466 Fax: (65) 6741 4666

Website: [www.quicseal.com](http://www.quicseal.com) Co.Reg. No.: 198201286W



## 15. REGULATORY INFORMATION

### Applicable National Regulations

This product is subject to the requirements in the following acts/regulations:

Workplace Safety and Health Act & Workplace Safety and Health (General Provisions) Regulations  
Environmental Protection and Management Act and Environmental Protection and Management  
Maritime and Port Authority of Singapore (Dangerous Goods, Petroleum and Explosives)

### International Regulations

This product is classified as hazardous pursuant to the provision set forth in Directives 67/548/EEC and 1999/45/EC and/or EC Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of EC Regulation 1907/2006 and subsequent amendments.

## 16. OTHER INFORMATION

The information and data contained herein are believed to be accurate and reliable; however, it is the user's responsibility to determine suitability of use. Since QUICSEAL Construction Chemicals Pte. Ltd. cannot know all of the uses to which its products may be put or the conditions of use; it makes no warranties concerning the fitness or suitability of its products for a particular use of purpose.

### QUICSEAL CONSTRUCTION CHEMICALS PTE LTD

No. 7 Eunos Avenue 8A Eunos Industrial Estate Singapore 409460 Tel: (65) 6742 4466 Fax: (65) 6741 4666

Website: [www.quicseal.com](http://www.quicseal.com) Co.Reg. No.: 198201286W





**SAFETY DATA SHEET  
QUICSEAL 135 – PART B  
EPOXY PRIMER, SOLVENT-FREE**

**1. INFORMATION OF THE SUBSTANCE/COMPOUND AND THE SUPPLIER**

Product Name: QUICSEAL 135 – Epoxy Primer, Solvent-free (Part B)  
Product Use: Primer for epoxy flooring system and polyurethane coating

Details of the supplier:

*QUICSEAL CONSTRUCTION CHEMICALS PTE LTD  
No. 7 Eunos Avenue 8A  
Eunos Industrial Estate  
Singapore 409460*

Emergency Contact No.: (65) 6742 4466

**2. HAZARDS IDENTIFICATION**

**GHS Classification:**

Acute oral toxicity – Category 4  
Skin corrosion – Category 1  
Serious eye damage – Category 1  
Skin sensitization – Category 1

**GHS LABEL ELEMENTS**

**Symbol(s):**



**Signal Word**

Danger

**Hazard Statements:**

H302: Harmful if swallowed  
H314: Causes severe skin burns  
H317: May cause an allergic skin reaction  
H318: Causes serious eye damage

**Precautionary Statements:**

Prevention

P260: Do not breathe fume/mist/vapours/spray.  
P264: Wash hands and forearms thoroughly after handling.  
P270: Do not eat, drink or smoke when using this product.  
P272: Contaminated work clothing should not be allowed out of the workplace.  
P280: Wear protective gloves/protective clothing/eye protection/face protection.

**QUICSEAL CONSTRUCTION CHEMICALS PTE LTD**

No. 7 Eunos Avenue 8A Eunos Industrial Estate Singapore 409460 Tel: (65) 6742 4466 Fax: (65) 6741 4666

Website: [www.quicseal.com](http://www.quicseal.com) Co.Reg. No.: 198201286W





Response

P301+P330+P331: IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

P303+P361+P353: IF ON SKIN (or hair): Remove/ Take off immediately all contaminated clothing. Rinse skin with water/ shower.

P304+P340: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P333+P313: If skin or rash occurs: Get medical advice/attention.

P363: Wash contaminated clothing before reuse

Storage

P405: Store locked up.

Disposal

P501: Dispose of contents/container in accordance with local/national regulations.

**3. COMPOSITION / INFORMATION ON INGREDIENTS**

This product contains the following components classified as hazardous:

COMPONENTS	CAS No.	EINECS No.	Index No.	Percentage
3-Aminomethyl-3,5,5-trimethylcyclohexylamine	2855-13-2	220-666-8	612-067-00-9	> 20%
Benzyl alcohol	100-51-6	202-859-9	--	> 25%

**4. FIRST-AID MEASURES****General information**

Take person to a safe place. Observe self-protection for first aid. Always seek medical advice in the event of contact with this substance.

**Inhalation**

Keep the patient calm. If unconscious place in stable sideways position. Protect against loss of body heat. If breathing stops, administer artificial respiration. Seek medical advice immediately and clearly identify substance.

**Skin contact**

Remove contaminated clothes at once. Wash off contaminated skin with plenty of water and soap immediately for 10-15 minutes. In serious cases, use emergency shower immediately. Seek medical advice immediately and clearly identify substance.

**Eye contact**

Rinse immediately with plenty of water for 10-15 minutes. Remove any contact lenses and keep eyelids well open to rinse the whole eye surface and eyelids with water. Seek medical advice immediately and clearly identify substance. Continue to bathe eyes during transport to medical practitioner.

**QUICSEAL CONSTRUCTION CHEMICALS PTE LTD**

No. 7 Eunos Avenue 8A Eunos Industrial Estate Singapore 409460 Tel: (65) 6742 4466 Fax: (65) 6741 4666

Website: [www.quicseal.com](http://www.quicseal.com) Co.Reg. No.: 198201286W



**Ingestion**

If conscious, give several small portions of water to drink. Induce vomiting. Call a physician or poison control immediately. NEVER give anything by mouth to an unconscious person. NEVER induce vomiting in an unconscious person.

**Notes to physician**

Treat patient symptomatically (decontamination, vital functions).

**5. FIRE-FIGHTING MEASURES****General Fire Hazards**

This product is classified as non-combustible hence is not considered a fire risk. However if the product is involved in fire, fumes of carbon oxides (COx) and nitrogen oxides (NOx) may be liberated.

**Fire-fighting Procedures / Advice for fire-fighters**

Evacuate area immediately. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Deluge with large quantities of water as quickly as possible from a protected location. Avoid impact, friction, heat, or flam during fire-fighting.

**Suitable Fire-extinguishing Media**

Extinguish with alcohol-resistant foam, carbon dioxide, or dry powder.

**Hazardous Combustion Products**

Carbon oxides (COx) and nitrogen oxides (NOx) as thermal decomposition products.

**Further information**

Dispose of fire debris and contaminated extinguishing water in accordance with official regulations.

**6. ACCIDENTAL RELEASE MEASURES****Emergency Measures**

Emergency and non-emergency responders should use personal protective equipment. Avoid contact with skin and eyes. Do not breathe vapours/aerosol.

**Personal Precautions and Protective equipment**

Response and clean-up crews must be properly trained and must utilize proper protective equipment (see Section 8).

**Environmental Precautions**

Protect bodies of water by diking, absorbents, or absorbent boom, if possible. Do not flush down sewer or drainage systems, unless system is designed and permitted to handle such material.

**Methods and materials for containment and cleaning up**

Carefully contain and stop the source of the spill, if safe to do so. Clean up spills immediately using soft natural bristle brush and conductive rubber or conductive plastic shovel. Use caution; material is sensitive to initiation from sources such as heat, flame, shock, friction, or sparks. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Keep in suitable and closed containers for disposal. Clean contaminated surface thoroughly.

**QUICSEAL CONSTRUCTION CHEMICALS PTE LTD**

No. 7 Eunos Avenue 8A Eunos Industrial Estate Singapore 409460 Tel: (65) 6742 4466 Fax: (65) 6741 4666

Website: [www.quicseal.com](http://www.quicseal.com) Co.Reg. No.: 198201286W



## 7. HANDLING AND STORAGE

### Precautions for Safe Handling

Avoid all personal contact, including inhalation. Wear protective clothing when risk of exposure occurs. Do not allow clothing to be wet with product. Avoid contact with moisture and incompatible materials. When handling, do not eat, drink or smoke. Keep containers securely sealed when not in use and avoid physical damage to containers. Always wash hands with soap and water after handling. Work clothes should be laundered separately. Launder contaminated clothing before re-use. Observe manufacturer's storing and handling recommendations. Atmosphere should be regularly checked against established exposure standards to ensure safe working conditions are maintained.

### Conditions for safe storage, including any incompatibilities

Store in original container. Check all containers are clearly-labelled and free from leaks. Keep containers securely sealed. Store in a cool, dry, well-ventilated area. The product is sensitive to moisture and carbon dioxide, store under inert gas. Keep away from incompatible materials (strong acids, strong oxidizers, epoxides) and foodstuff containers. Protect containers against physical damage and check regularly for leaks.

## 8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

### Control parameters / Occupational Exposure Limits

This product contains no component that has relevant occupational exposure limits.

### Appropriate engineering control measures

There are no specific engineering control measures necessary for this product. However, it is of good practice to use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels of fumes.

### Personal Protective Equipment

Eye protection: Safety glasses

Hand Protection: Impervious gloves

Respiratory Protection: Appropriate respiratory protection is required when exposure to airborne contaminants may exceed acceptable limits. Respirators should be selected and used in accordance with OSHA, Subpart I (29 CFR 1910.134) and manufacturer's recommendations.

Body Protection: Flame retardant clothing. Wear conductive safety shoes.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state: Liquid

Color: Colorless

Odour: Ammoniacal

Flash Point: 107°C

Boiling point: 195°C

Water Solubility (25°C): Partially soluble in water  
Fully soluble in alcohols, glycolethers and aromatic hydrocarbons

Specific Gravity: Approx. 1.02

Viscosity: 300 mPa.s

## QUICSEAL CONSTRUCTION CHEMICALS PTE LTD

No. 7 Eunos Avenue 8A Eunos Industrial Estate Singapore 409460 Tel: (65) 6742 4466 Fax: (65) 6741 4666

Website: [www.quicseal.com](http://www.quicseal.com) Co.Reg. No.: 198201286W



## 10. STABILITY AND REACTIVITY

### Product Stability

The product is stable under recommended handling and storage conditions.

### Possibility of hazardous reactions

The product reacts with acids, strong oxidizing agents, and epoxides.

### Conditions to avoid

Keep away from places/environment saturated with moisture and carbon dioxide. Keep away from flame, sparks, static electricity, or other sources of ignition.

### Incompatible materials

Oxidizing agents, alkalis and amines and strong sunlight or ultraviolet light.

### Hazardous decomposition products

None under normal use. Carbon Carbon dioxide, nitrogen oxides, and other pyrolysis products typical of burning organic material may be liberated when product is involved in fire.

## 11. TOXICOLOGICAL INFORMATION

This product has not been tested and all the toxicological statements have been derived from the respective components' available toxicity information.

### Acute toxicity

Experimental/calculated data:

LD50, oral: 2,500 mg/kg (the product may be harmful if ingested)

LD50, dermal: > 5,000 mg/kg (the product is non-harmful/non-toxic on contact with skin)

LC50, inhalation: > 20 mg/L (the product is non-harmful/non-toxic if inhaled)

### Skin and Eye Irritation

This product causes severe skin burns and serious eye damage.

3-Aminomethyl-3,5,5-trimethylcyclohexylamine, CAS No.: 2855-13-2 - Skin corrosive (Category 1)  
- Eye corrosive (Category 1)

Benzyl alcohol, CAS No.: 100-51-6 – Eye irritant (Category 2)

### Respiratory / Skin sensitization

The product's components may cause an allergic skin reaction. This product is not expected to cause allergy or asthma symptoms or breathing difficulties if accidentally inhaled.

### Germ cell mutagenicity / Carcinogenicity / Reproductive toxicity / Developmental toxicity

Based on the assessment of available information, the product is: not mutagenic in bacteria; has no known carcinogenic effect; and not expected to cause reproductive and developmental toxicity.

### Specific target organ toxicity (single and repeated exposure)

Based on the available information, there is no specific target organ toxicity expected after a single or repeated exposure to the product.

## QUICSEAL CONSTRUCTION CHEMICALS PTE LTD

No. 7 Eunos Avenue 8A Eunos Industrial Estate Singapore 409460 Tel: (65) 6742 4466 Fax: (65) 6741 4666

Website: [www.quicseal.com](http://www.quicseal.com) Co.Reg. No.: 198201286W



## 12. ECOLOGICAL INFORMATION

### Ecotoxicity

Based on the ecological assessment of the product's components, this product is not expected to be toxic/harmful to aquatic life on both short-term and long-term duration.

### Additional information

Do not release product untreated into natural waters. At the present knowledge of the product, no negative ecological effects are expected.

## 13. DISPOSAL CONSIDERATIONS

### Description of waste residues and information on their safe handling & methods of disposal

Dispose of the product through licensed hazardous waste collectors under Singapore regulations. Provide the hazardous waste collector the sufficient information on the various hazards of this product.

### Disposal of any contaminated packaging

Dried material can be disposed off in authorized landfill site in accordance to national regulations. Container should be recycled after cleaning or dispose of the container through licensed hazardous waste collectors under Singapore regulations. Provide the hazardous waste collector the sufficient information on the various hazards of this product in this container.

## 14. TRANSPORT INFORMATION

### Land Transport (ADR/RID):

Shipping Name: Amines or polyamines, liquid, corrosive, n.o.s.  
(contains 3-aminomethyl-3,5,5-trimethylcyclohexylamine)

UN #: 2735

Hazard Class: 8 Letter: 53c

Packing Group: III

1st numbering of tanks panel: 80

2nd numbering of tanks panel: 2735

### Air Transport (IATA/ICAO):

Shipping Name: Amines or polyamines, liquid, corrosive, n.o.s.  
(contains 3-aminomethyl-3,5,5-trimethylcyclohexylamine)

UN #: 2735

Hazard Class: 8

Packing Group: III

Packing Instructions (passenger aircraft): 818

Packing Instructions (cargo air only): 820

### Sea transport (IMDG):

Shipping Name: Amines or polyamines, liquid, corrosive, n.o.s.  
(contains 3-aminomethyl-3,5,5-trimethylcyclohexylamine)

UN #: 2735

Hazard Class: 8

Packing Group: III

EmS: 8-05 MFAG: 820

Marine pollutant: No

## QUICSEAL CONSTRUCTION CHEMICALS PTE LTD

No. 7 Eunos Avenue 8A Eunos Industrial Estate Singapore 409460 Tel: (65) 6742 4466 Fax: (65) 6741 4666

Website: [www.quicseal.com](http://www.quicseal.com) Co.Reg. No.: 198201286W



## 15. REGULATORY INFORMATION

### Applicable National Regulations

This product is subject to the requirements in the following acts/regulations:

Workplace Safety and Health Act & Workplace Safety and Health (General Provisions) Regulations  
Environmental Protection and Management Act and Environmental Protection and Management  
Maritime and Port Authority of Singapore (Dangerous Goods, Petroleum and Explosives)

### International Regulations

This product is classified as hazardous pursuant to the provision set forth in Directives 67/548/EEC and 1999/45/EC and/or EC Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of EC Regulation 1907/2006 and subsequent amendments.

## 16. OTHER INFORMATION

The information and data contained herein are believed to be accurate and reliable; however, it is the user's responsibility to determine suitability of use. Since QUICSEAL Construction Chemicals Pte. Ltd. cannot know all of the uses to which its products may be put or the conditions of use; it makes no warranties concerning the fitness or suitability of its products for a particular use of purpose.

### QUICSEAL CONSTRUCTION CHEMICALS PTE LTD

No. 7 Eunos Avenue 8A Eunos Industrial Estate Singapore 409460 Tel: (65) 6742 4466 Fax: (65) 6741 4666

Website: [www.quicseal.com](http://www.quicseal.com) Co.Reg. No.: 198201286W

