



**SAFETY DATA SHEET  
QUICSEAL 304 – PART A  
EPOXY PUTTY**

**1. INFORMATION OF THE SUBSTANCE/COMPOUND AND THE SUPPLIER**

Product Name: QUICSEAL 304 – Epoxy Putty (Part A)  
Product Use: Part A of a two-component epoxy putty

Details of the supplier:

*QUICSEAL CONSTRUCTION CHEMICALS PTE LTD  
No. 7 Eunos Avenue 8A  
Eunos Industrial Estate  
Singapore 409460*

Emergency Contact No.: (65) 6742 4466

**2. HAZARDS IDENTIFICATION**

**GHS Classification:**

Skin irritation – Category 2  
Eye irritation – Category 2  
Skin sensitization – Category 1  
Chronic aquatic toxicity – Category 2

**GHS LABEL ELEMENTS**

**Symbol(s):**



**Signal Word**

Warning

**Hazard Statements:**

H315: Causes skin irritation  
H319: Causes serious eye irritation  
H317: May cause an allergic skin reaction  
H411: Toxic to aquatic life with long lasting effects.

**Precautionary Statements:**

Prevention

P261: Avoid breathing fume/mist/vapours/spray.  
P264: Wash hands and forearms thoroughly after handling.  
P272: Contaminated work clothing should not be allowed out of the workplace.  
P273: Avoid release to the environment.  
P280: Wear protective gloves/protective clothing/eye protection/face protection.

**QUICSEAL CONSTRUCTION CHEMICALS PTE LTD**

No. 7 Eunos Avenue 8A Eunos Industrial Estate Singapore 409460 Tel: (65) 6742 4466 Fax: (65) 6741 4666

Website: [www.quicseal.com](http://www.quicseal.com) Co.Reg. No.: 198201286W



Response

P302+P352: IF ON SKIN: Wash with plenty of soap and water.

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center or doctor/physician.

P333+P313: If skin irritation or rash occurs: Get medical advice/attention.

P337+P313: If eye irritation persists: Get medical advice/attention.

P363: Take off contaminated clothing and wash before reuse.

P391: Collect spillage.

Disposal

P501: Dispose of contents/container in accordance with local/national regulations.

**3. COMPOSITION / INFORMATION ON INGREDIENTS**

This product contains the following components classified as hazardous:

COMPONENTS	CAS No.	EINECS No.	Index No.	Percentage
Bisphenol A epoxy resin	25068-38-6	500-033-5	603-074-00-8	Proprietary
C12-C14 aliphatic diglycidyl ether	68609-97-2	271-846-8	603-103-00-4	Proprietary

**4. FIRST-AID MEASURES****General information**

Take person to a safe place. Observe self-protection for first aid. Always seek medical advice in the event of contact with this substance.

**Inhalation**

Keep the patient calm. If unconscious place in stable sideways position. Protect against loss of body heat. If breathing stops, administer artificial respiration. Seek medical advice immediately and clearly identify substance.

**Skin contact**

Remove contaminated clothes at once. Wash off with plenty of water or water and soap immediately for 10-15 minutes. In serious cases, use emergency shower immediately. Seek medical advice immediately and clearly identify substance.

**Eye contact**

Rinse immediately with plenty of water for 10-15 minutes. Keep eyelids well open to rinse the whole eye surface and eyelids with water. Seek medical advice immediately and clearly identify substance. Continue to bathe eyes during transport to medical practitioner.

**Ingestion**

If conscious, give several small portions of water to drink. Do not induce vomiting. Seek medical advice immediately and clearly identify substance.

**Notes to physician**

Treat patient symptomatically (decontamination, vital functions).

**QUICSEAL CONSTRUCTION CHEMICALS PTE LTD**

No. 7 Eunos Avenue 8A Eunos Industrial Estate Singapore 409460 Tel: (65) 6742 4466 Fax: (65) 6741 4666

Website: [www.quicseal.com](http://www.quicseal.com) Co.Reg. No.: 198201286W



## 5. FIRE-FIGHTING MEASURES

### General Fire Hazards

The product is non-flammable. If material is involved in fire, do not breathe fumes.

### Suitable Fire-extinguishing Media

Use the appropriate fire extinguishing media for surrounding fire (water, foam, dry powder, CO<sub>2</sub>)

### Hazardous Combustion Products

Carbon monoxide, carbon dioxide and non-combusted hydrocarbons (smoke).

### Advice for fire-fighters

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Do not use a solid water stream as it may scatter and spread fire.

### Further information

Dispose of fire debris and contaminated extinguishing water in accordance with official regulations.

## 6. ACCIDENTAL RELEASE MEASURES

### Emergency Measures

Emergency and non-emergency responders should use personal protective equipment. Avoid contact with skin and eyes. Do not breathe vapours/aerosol.

### Personal Precautions and Protective equipment

Response and clean-up crews must be properly trained and must utilize proper protective equipment (see Section 8).

### Environmental Precautions

Protect bodies of water by diking, absorbents, or absorbent boom, if possible. Do not flush down sewer or drainage systems, unless system is designed and permitted to handle such material.

### Methods and materials for containment and cleaning up

Carefully contain and stop the source of the spill, if safe to do so.

Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).

Keep in suitable and closed containers for disposal. Clean contaminated surface thoroughly.

## 7. HANDLING AND STORAGE

### Precautions for Safe Handling

Plan first aid action before beginning work with this product. Wear personal protective equipment. Avoid contact with skin and eyes.

### Conditions for safe storage, including any incompatibilities

Keep out of reach of children. Store in a place accessible by authorized persons only. Store in original container. Keep tightly closed in a dry and cool place. Shelf life up to 2 years from date of manufacture.

## QUICSEAL CONSTRUCTION CHEMICALS PTE LTD

No. 7 Eunos Avenue 8A Eunos Industrial Estate Singapore 409460 Tel: (65) 6742 4466 Fax: (65) 6741 4666

Website: [www.quicseal.com](http://www.quicseal.com) Co.Reg. No.: 198201286W



## 8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

### Control Parameters / Occupational Exposure Limits

For component: C12-C14 aliphatic diglycidyl ether, CAS No.: 68609-97-2  
Singapore Permissible Exposure Level (PEL), long term: 0.1 ppm / 0.54 mg/m<sup>3</sup>

### Occupational Exposure Controls

Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes and clothing.

### Personal Protective Equipment:

#### Hand Protection

Protective gloves complying with EN 374. Gloves made of Nitril.  
Break through time: > 4 h.

#### Eye Protection

Safety glasses with side-shields conforming to EN 166. Eye wash bottle with pure water.

#### Skin / Body Protection

Long sleeved clothing. Choose body protection according to the amount and concentration of the dangerous substance at the work place.

#### Respiratory Protection

No personal respiratory protective equipment normally required. Breathing apparatus needed only when aerosol or mist is formed. Respirator with A/P2 filter.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state:	Paste
Color:	Grey
Odour:	Slight/faint
Flash Point:	> 150°C
Initial boiling point and boiling range:	Not available
Freezing / Melting point:	Not available
Autoignition temperature:	Not available
Flammability Limits:	Not available
Vapor pressure (20°C):	Not available
Vapor density:	Not available
Water Solubility (25°C):	Not soluble
Specific Gravity:	1.6 – 1.7

## 10. STABILITY AND REACTIVITY

### Chemical stability

Stable at normal conditions. No decomposition if stored and applied as directed.

## QUICSEAL CONSTRUCTION CHEMICALS PTE LTD

No. 7 Eunos Avenue 8A Eunos Industrial Estate Singapore 409460 Tel: (65) 6742 4466 Fax: (65) 6741 4666

Website: [www.quicseal.com](http://www.quicseal.com) Co.Reg. No.: 198201286W



**Possibility of hazardous reactions**

No hazardous reactions are expected under normal conditions of handling and storage. Keep away from oxidising agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

**Conditions to avoid**

Avoid temperatures above 60°C, direct sunlight and contact with sources of heat. Burning produces obnoxious and toxic fumes.

**Incompatible materials**

Oxidising agents, strongly alkaline and strongly acid materials.

**Hazardous decomposition products**

None under normal use. Carbon monoxide, carbon dioxide and non-combusted hydrocarbons (smoke) may be liberated when product is involved in fire.

**11. TOXICOLOGICAL INFORMATION**

This product has not been tested and all the toxicological statements have been derived from the respective components' available toxicity information.

**Acute toxicity**

Experimental/calculated data:

LD50, oral: > 5,000 mg/kg (the product is not toxic/harmful if ingested)

LD50, dermal: > 5,000 mg/kg (the product is not toxic/harmful on contact with skin)

LC50, inhalation: > 20 mg/L (the product is not toxic/harmful if inhaled)

**Skin and Eye Irritation**

The product contains the following components with their respective skin and eye corrosion/irritation classification:

COMPONENTS	CAS No.	Animal skin test result	Animal eye test result
Bisphenol A epoxy resin	25068-38-6	Moderate Irritant (Skin Irritant Category 2)	Moderate Irritant (Eye Irritant Category 2)
C12-C14 aliphatic diglycidyl ether	68609-97-2	Moderate Irritant (Skin Irritant Category 2)	Moderate Irritant (Eye Irritant Category 2)

**Respiratory / Skin sensitization**

The product's components may cause an allergic skin reaction. This product is not expected to cause allergy or asthma symptoms or breathing difficulties if accidentally inhaled.

**Germ cell mutagenicity / Carcinogenicity / Reproductive toxicity / Developmental toxicity**

Based on the assessment of available information, the product is: not mutagenic in bacteria; has no known carcinogenic effect; and not expected to cause reproductive and developmental toxicity.

**Specific target organ toxicity (single and repeated exposure)**

Based on the available information, there is no specific target organ toxicity expected after a single or repeated exposure to the product.

**QUICSEAL CONSTRUCTION CHEMICALS PTE LTD**

No. 7 Eunos Avenue 8A Eunos Industrial Estate Singapore 409460 Tel: (65) 6742 4466 Fax: (65) 6741 4666

Website: [www.quicseal.com](http://www.quicseal.com) Co.Reg. No.: 198201286W



## 12. ECOLOGICAL INFORMATION

The following ecological assessment is based on the available ecotoxicity information of the product's components.

### Chronic toxicity to the aquatic environment

The product's major components are classified as Category 2 chronic aquatic toxicants. By estimation this product is considered toxic to aquatic life with long lasting effects (Chronic toxicity to the aquatic environment Category 2)

## 13. DISPOSAL CONSIDERATIONS

### Description of waste residues and information on their safe handling & methods of disposal

Dispose of the product through licensed hazardous waste collectors under Singapore regulations. Provide the hazardous waste collector the sufficient information on the various hazards of this product.

### Disposal of any contaminated packaging

Dried material can be disposed off in authorized landfill site in accordance to national regulations. Container should be recycled after cleaning or dispose of the container through licensed hazardous waste collectors under Singapore regulations. Provide the hazardous waste collector the sufficient information on the various hazards of this product in this container.

## 14. TRANSPORT INFORMATION

### Land Transport (ADR):

Proper Shipping Name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S., MIXTURE (Epoxy resin)

UN Number: 3082  
Hazard Class: 9  
Packing Group: III

### Air Transport (IATA):

Proper Shipping Name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S., MIXTURE (Epoxy resin)

UN Number: 3082  
Hazard Class: 9  
Packing Group: III  
Packing instructions: Passenger aircraft: 964 (450 L)  
LQ: Y964 (30 kg G)  
Cargo aircraft: 964 (450 L)

### Sea transport (IMDG):

Proper Shipping Name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S., MIXTURE (Epoxy resin)

UN Number: 3082  
Hazard Class: 9  
Packing Group: III  
EmS Number: F-A S-F  
Marine pollutant: Yes

## QUICSEAL CONSTRUCTION CHEMICALS PTE LTD

No. 7 Eunos Avenue 8A Eunos Industrial Estate Singapore 409460 Tel: (65) 6742 4466 Fax: (65) 6741 4666

Website: [www.quicseal.com](http://www.quicseal.com) Co.Reg. No.: 198201286W



## 15. REGULATORY INFORMATION

### Applicable National Regulations

This product is subject to the requirements in the following acts/regulations:

Workplace Safety and Health Act & Workplace Safety and Health (General Provisions) Regulations  
Environmental Protection and Management Act and Environmental Protection and Management  
Maritime and Port Authority of Singapore (Dangerous Goods, Petroleum and Explosives)

### International Regulations

This product is classified as hazardous pursuant to the provision set forth in Directives 67/548/EEC and 1999/45/EC and/or EC Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of EC Regulation 1907/2006 and subsequent amendments.

## 16. OTHER INFORMATION

The information and data contained herein are believed to be accurate and reliable; however, it is the user's responsibility to determine suitability of use. Since QUICSEAL Construction Chemicals Pte. Ltd. cannot know all of the uses to which its products may be put or the conditions of use; it makes no warranties concerning the fitness or suitability of its products for a particular use of purpose.

### QUICSEAL CONSTRUCTION CHEMICALS PTE LTD

No. 7 Eunos Avenue 8A Eunos Industrial Estate Singapore 409460 Tel: (65) 6742 4466 Fax: (65) 6741 4666

Website: [www.quicseal.com](http://www.quicseal.com) Co.Reg. No.: 198201286W





**SAFETY DATA SHEET  
QUICSEAL 304 – PART B  
EPOXY PUTTY**

**1. INFORMATION OF THE SUBSTANCE/COMPOUND AND THE SUPPLIER**

Product Name: QUICSEAL 304 – Epoxy Putty (Part B)  
Product Use: Part B of a two-component epoxy putty

Details of the supplier:

*QUICSEAL CONSTRUCTION CHEMICALS PTE LTD  
No. 7 Eunos Avenue 8A  
Eunos Industrial Estate  
Singapore 409460*

Emergency Contact No.: (65) 6742 4466

**2. HAZARDS IDENTIFICATION**

**GHS Classification:**

Skin corrosion – Category 1  
Serious eye damage – Category 1

**GHS LABEL ELEMENTS**

**Symbol(s):**



**Signal Word**

Danger

**Hazard Statements:**

H314: Causes severe skin burns and eye damage  
H318: Causes serious eye damage

**Precautionary Statements:**

Prevention

P260: Do not breathing fume/mist/vapours/spray.  
P264: Wash hands and forearms thoroughly after handling.  
P280: Wear protective gloves/protective clothing/eye protection/face protection.

**QUICSEAL CONSTRUCTION CHEMICALS PTE LTD**

No. 7 Eunos Avenue 8A Eunos Industrial Estate Singapore 409460 Tel: (65) 6742 4466 Fax: (65) 6741 4666

Website: [www.quicseal.com](http://www.quicseal.com) Co.Reg. No.: 198201286W





Response

P301+P330+P331: IF SWALLOWED: Rinse mouth, Do NOT induce vomiting.

P303+P361+P353: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P304+P340: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center or doctor/physician.

Storage

P405: Store locked up.

Disposal

P501: Dispose of contents/container in accordance with local/national regulations.

**3. COMPOSITION / INFORMATION ON INGREDIENTS**

This product contains the following components classified as hazardous:

COMPONENTS	CAS No.	EINECS No.	Index No.	Percentage
Triethylenetetramine	112-24-3	203-950-6	612-059-00-5	Proprietary
Tris-2.4.6-(Dimethylaminomethyl)phenol	90-72-2	--	--	Proprietary

**4. FIRST-AID MEASURES****General information**

Take person to a safe place. Observe self-protection for first aid. Always seek medical advice in the event of contact with this substance.

**Inhalation**

Keep the patient calm. If unconscious place in stable sideways position. Protect against loss of body heat. If breathing stops, administer artificial respiration. Seek medical advice immediately and clearly identify substance.

**Skin contact**

Remove contaminated clothes at once. Wash off with plenty of water or water and soap immediately for 10-15 minutes. In serious cases, use emergency shower immediately. Seek medical advice immediately and clearly identify substance.

**Eye contact**

Rinse immediately with plenty of water for 10-15 minutes. Remove any contact lenses and keep eyelids well open to rinse the whole eye surface and eyelids with water. Seek medical advice immediately and clearly identify substance. Continue to bathe eyes during transport to medical practitioner.

**QUICSEAL CONSTRUCTION CHEMICALS PTE LTD**

No. 7 Eunos Avenue 8A Eunos Industrial Estate Singapore 409460 Tel: (65) 6742 4466 Fax: (65) 6741 4666

Website: [www.quicseal.com](http://www.quicseal.com) Co.Reg. No.: 198201286W



**Ingestion**

If conscious, give several small portions of water to drink. Induce vomiting. Call a physician or poison control immediately. NEVER give anything by mouth to an unconscious person. NEVER induce vomiting in an unconscious person.

**Notes to physician**

Treat patient symptomatically (decontamination, vital functions).

**5. FIRE-FIGHTING MEASURES****Fire-fighting Procedures / Advice for fire-fighters**

Evacuate area immediately. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Deluge with large quantities of water as quickly as possible from a protected location. Avoid impact, friction, heat, or flam during fire-fighting.

**Suitable Fire-extinguishing Media**

Extinguish with alcohol-resistant foam, carbon dioxide, or dry powder.

**Hazardous Combustion Products**

Carbon monoxide, carbon dioxide, nitrogen, water, hydrogen, nitrogen oxides, methane, aldehydes, carboxylic acids, and hydrogen cyanide.

**Further information**

Dispose of fire debris and contaminated extinguishing water in accordance with official regulations.

**6. ACCIDENTAL RELEASE MEASURES****Emergency Measures, Personal Precautions and Protective equipment**

Emergency and non-emergency responders should use personal protective equipment. Avoid contact with skin and eyes. Do not breathe vapours/aerosol. Response and clean-up crews must be properly trained and must utilize proper protective equipment (see Section 8).

**Environmental Precautions**

Protect bodies of water by diking, absorbents, or absorbent boom, if possible. Do not flush down sewer or drainage systems, unless system is designed and permitted to handle such material.

**Methods and materials for containment and cleaning up**

Carefully contain and stop the source of the spill, if safe to do so.

Clean up spills immediately using soft natural bristle brush and conductive rubber or conductive plastic shovel. Use caution; material is sensitive to initiation from sources such as heat, flame, shock, friction, or sparks. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Keep in suitable and closed containers for disposal. Clean contaminated surface thoroughly.

**QUICSEAL CONSTRUCTION CHEMICALS PTE LTD**

No. 7 Eunos Avenue 8A Eunos Industrial Estate Singapore 409460 Tel: (65) 6742 4466 Fax: (65) 6741 4666

Website: [www.quicseal.com](http://www.quicseal.com) Co.Reg. No.: 198201286W



## 7. HANDLING AND STORAGE

### Precautions for Safe Handling

Plan first aid action before beginning work with this product. Wear personal protective equipment. Avoid contact with skin and eyes.

### Conditions for safe storage, including any incompatibilities

Do not pressurize or expose containers to heat, flame, sparks, static electricity, or other sources of ignition. Store in a cool, dry place (approximately 20°C). Store only in approved containers. Check old products for deterioration regularly. Avoid storing product near incompatible materials (see Section 10). Do not store near flammable materials. Do not keep deteriorated or salvaged product. Do not store in direct sunlight or exposure to UV radiation.

## 8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

### Control Parameters / Occupational Exposure Limits

This product contains no components with relevant occupational exposure limits.

### Occupational Exposure Controls

Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes and clothing. Do NOT smoke in areas where product is stored or used. Material is shock sensitive. Use care in handling. Keep away from ignition sources. Friction can cause ignition. Eyewash fountains and safety showers should be easily accessible. Prevent build-up of static electric charges. Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits.

### Personal Protective Equipment

Eye protection: Safety glasses

Hand Protection: Impervious gloves

Respiratory Protection: Appropriate respiratory protection is required when exposure to airborne contaminants may exceed acceptable limits. Respirators should be selected and used in accordance with OSHA, Subpart I (29 CFR 1910.134) and manufacturer's recommendations.

Body Protection: Flame retardant clothing. Wear conductive safety shoes.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state:	Paste
Color:	Greyish black
Odour:	Slight
Flash Point:	>105°C
Initial boiling point and boiling range:	Not available
Autoignition temperature:	Not available
Flammability Limits:	Not available
Vapor pressure (20°C):	Not available
Vapor density:	Not available
Water Solubility (25°C):	Not soluble
Specific Gravity:	1.9 – 2.0

## QUICSEAL CONSTRUCTION CHEMICALS PTE LTD

No. 7 Eunos Avenue 8A Eunos Industrial Estate Singapore 409460 Tel: (65) 6742 4466 Fax: (65) 6741 4666

Website: [www.quicseal.com](http://www.quicseal.com) Co.Reg. No.: 198201286W



## 10. STABILITY AND REACTIVITY

### Product Stability

The product is stable under recommended handling and storage conditions.

### Possibility of hazardous reactions

The product strongly reacts with oxidising agents, strongly alkaline and strongly acid materials.

### Conditions to avoid

Keep away from heat, flame, sparks, static electricity, or other sources of ignition.

### Incompatible materials

Oxidizing agents, alkalis and amines and strong sunlight or ultraviolet light.

### Hazardous decomposition products

None under normal use. Carbon monoxide, carbon dioxide, nitrogen, water, hydrogen, nitrogen oxides, methane, aldehydes, carboxylic acids, and hydrogen cyanide. may be liberated when product is involved in fire.

## 11. TOXICOLOGICAL INFORMATION

This product has not been tested and all the toxicological statements have been derived from the respective components' available toxicity information.

### Acute toxicity

Experimental/calculated data:

LD50, oral: 3,700 mg/kg (the product is not classified as orally toxic)

LD50, dermal: 1,100 mg/kg (the product is harmful in contact with skin)

LC50, inhalation: > 20 mg/L (the product is classified as non-toxic if inhaled)

### Skin and Eye Irritation

This product causes severe skin corrosion and serious eye damage due to the following components:

Triethylenetetramine, CAS No.: 112-24-3 – Skin Corrosive (Category 1)

Tris-2.4.6-(Dimethylaminomethyl)phenol, CAS No.: 90-72-2 – Skin / Eye Corrosive (Category 1)

### Respiratory / Skin sensitization

The product's components may cause an allergic skin reaction. This product is not expected to cause allergy or asthma symptoms or breathing difficulties if accidentally inhaled.

### Germ cell mutagenicity / Carcinogenicity / Reproductive toxicity / Developmental toxicity

Based on the assessment of available information, the product is: not mutagenic in bacteria; has no known carcinogenic effect; and not expected to cause reproductive and developmental toxicity.

### Specific target organ toxicity (single and repeated exposure)

Based on the available information, there is no specific target organ toxicity expected after a single or repeated exposure to the product.

## QUICSEAL CONSTRUCTION CHEMICALS PTE LTD

No. 7 Eunos Avenue 8A Eunos Industrial Estate Singapore 409460 Tel: (65) 6742 4466 Fax: (65) 6741 4666

Website: [www.quicseal.com](http://www.quicseal.com) Co.Reg. No.: 198201286W



## 12. ECOLOGICAL INFORMATION

The following ecological assessment is based on the available ecotoxicity information of the product's components.

### Chronic toxicity to the aquatic environment

The product's major component is classified as Category 3 chronic aquatic toxicant. By estimation this product is considered harmful to aquatic life with long lasting effects (Chronic toxicity to the aquatic environment Category 3)

## 13. DISPOSAL CONSIDERATIONS

### Description of waste residues and information on their safe handling & methods of disposal

Dispose of the product through licensed hazardous waste collectors under Singapore regulations. Provide the hazardous waste collector the sufficient information on the various hazards of this product.

### Disposal of any contaminated packaging

Dried material can be disposed off in authorized landfill site in accordance to national regulations. Container should be recycled after cleaning or dispose of the container through licensed hazardous waste collectors under Singapore regulations. Provide the hazardous waste collector the sufficient information on the various hazards of this product in this container.

## 14. TRANSPORT INFORMATION

### Land Transport (ADR):

Proper Shipping Name: TRIETHYLENETETRAMINE  
UN Number: 2259  
Hazard Class: 8  
Packing Group: II

### Air Transport (IATA):

Proper Shipping Name: TRIETHYLENETETRAMINE  
UN Number: 2259  
Hazard Class: 8  
Packing Group: II

### Sea transport (IMDG):

Proper Shipping Name: TRIETHYLENETETRAMINE  
UN Number: 2259  
Hazard Class: 8  
Packing Group: II  
Marine pollutant: No

## QUICSEAL CONSTRUCTION CHEMICALS PTE LTD

No. 7 Eunos Avenue 8A Eunos Industrial Estate Singapore 409460 Tel: (65) 6742 4466 Fax: (65) 6741 4666

Website: [www.quicseal.com](http://www.quicseal.com) Co.Reg. No.: 198201286W



## 15. REGULATORY INFORMATION

### Applicable National Regulations

This product is subject to the requirements in the following acts/regulations:

Workplace Safety and Health Act & Workplace Safety and Health (General Provisions) Regulations  
Environmental Protection and Management Act and Environmental Protection and Management  
Maritime and Port Authority of Singapore (Dangerous Goods, Petroleum and Explosives)

### International Regulations

This product is classified as hazardous pursuant to the provision set forth in Directives 67/548/EEC and 1999/45/EC and/or EC Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of EC Regulation 1907/2006 and subsequent amendments.

## 16. OTHER INFORMATION

The information and data contained herein are believed to be accurate and reliable; however, it is the user's responsibility to determine suitability of use. Since QUICSEAL Construction Chemicals Pte. Ltd. cannot know all of the uses to which its products may be put or the conditions of use; it makes no warranties concerning the fitness or suitability of its products for a particular use of purpose.

### QUICSEAL CONSTRUCTION CHEMICALS PTE LTD

No. 7 Eunos Avenue 8A Eunos Industrial Estate Singapore 409460 Tel: (65) 6742 4466 Fax: (65) 6741 4666

Website: [www.quicseal.com](http://www.quicseal.com) Co.Reg. No.: 198201286W

