



**SAFETY DATA SHEET
QUICSEAL 633T
SUPERSEAL**

1. IDENTIFICATION OF THE PRODUCT AND THE SUPPLIER

Product Name: QUICSEAL 633T – Superseal
Product Use: Solvent-based water-repellent impregnator for medium to high absorbency building materials

Details of the supplier:

*QUICSEAL CONSTRUCTION CHEMICALS PTE LTD
No. 7 Eunos Avenue 8A
Eunos Industrial Estate
Singapore 409460*

Emergency Contact No.: (65) 6742 4466

2. HAZARDS IDENTIFICATION

GHS Classification:

Flammable Liquid – Category 3
Eye Irritation – Category 2
Specific Target Organ Toxicity, single exposure – Category 3

GHS LABEL ELEMENTS

Symbol(s):



Signal Word

Warning

Hazard Statements:

H226: Flammable liquid and vapour
H319: Causes serious eye irritation
H336: May cause drowsiness or dizziness

Precautionary Statements:

Prevention

P210: Keep away from heat/sparks/open flames/hot surfaces. No smoking.
P233: Keep container tightly closed.
P240: Ground/bond container and receiving equipment.
P241: Use explosion-proof electrical/ventilating/lighting equipment.
P242: Take precautionary measures against static discharge.
P243: Use only non-sparking tools.
P261: Avoid breathing mist and fumes.

QUICSEAL CONSTRUCTION CHEMICALS PTE LTD

No. 7 Eunos Avenue 8A Eunos Industrial Estate Singapore 409460 Tel: (65) 6742 4466 Fax: (65) 6741 4666

Website: www.quicseal.com Co.Reg. No.: 198201286W



- P264: Wash hands and forearms thoroughly after handling.
 P271: Use only outdoors or in a well-ventilated area.
 P280: Wear protective gloves/protective clothing/eye protection/face protection.

Response

- P303+P361+P353: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
 P304+P340: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable to breathing.
 P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do so. Continue rinsing.
 P312: Call a POISON CENTER or doctor/physician if you feel unwell.
 P370+P378: In case of fire: Use appropriate extinction.
 P337+P313: If eye irritation persists: Get medical advice/attention.

Storage

- P403+P233/P235: Store in a well ventilated place. Keep container tightly closed. Keep cool.
 P405: Store locked up.

Disposal

- P501: Dispose of contents/container in accordance with local/national/international regulations.

3. COMPOSITION / INFORMATION ON INGREDIENTS

This product contains the following components classified as hazardous:

COMPONENTS	CAS No.	EINECS No.	Index No.	Percentage
Ethyl Acetate	141-78-6	205-500-4	607-022-00-5	79.3 – 83.4%
2-Propanol	67-63-0	200-661-7	603-117-00-0	11.1 – 12.7%
Solvent Naphtha (Petroleum) Medium	64742-88-7	265-191-7	649-405-00-X	6.7 – 7.8%

4. FIRST-AID MEASURES

General information

Take person to a safe place. Observe self-protection for first aid. Always seek medical advice in the event of contact with this substance.

Inhalation

Keep the patient calm. If unconscious place in stable sideways position. Protect against loss of body heat. If breathing stops, administer artificial respiration. Seek medical advice immediately and clearly identify substance.

Skin contact

Remove contaminated clothes at once. Wash off with plenty of water or water and soap immediately for 10-15 minutes. In serious cases, use emergency shower immediately. Seek medical advice immediately and clearly identify substance.

QUICSEAL CONSTRUCTION CHEMICALS PTE LTD

No. 7 Eunos Avenue 8A Eunos Industrial Estate Singapore 409460 Tel: (65) 6742 4466 Fax: (65) 6741 4666

Website: www.quicseal.com Co.Reg. No.: 198201286W



Eye contact

Rinse immediately with plenty of water for 10-15 minutes. Keep eyelids well open to rinse the whole eye surface and eyelids with water. Seek medical advice immediately and clearly identify substance. Continue to bathe eyes during transport to medical practitioner.

Ingestion

If conscious, give several small portions of water to drink. Do not induce vomiting. Seek medical advice immediately and clearly identify substance.

5. FIRE-FIGHTING MEASURES**General fire hazards**

This product is classified as FLAMMABLE LIQUID. See Section 9 for Flammability Properties.

Closed containers exposed to heat of a fire may lead to pressure rise and explode. Vapors may be ignited rapidly when exposed to heat, spark, open flame or other source of ignition. When mixed with air and exposed to an ignition source, flammable vapors can burn in the open or explode in confined spaces. Being heavier than air, vapors may travel long distances to an ignition source and flash back. Runoff to sewer may cause fire or explosion hazard.

Suitable Fire-extinguishing media: Dry chemical, carbon dioxide, sand, fire fighting foam.

Fire-fighting equipment / instructions

Small fires in the incipient (beginning) stage may typically be extinguished using handheld portable fire extinguishers and other fire fighting equipment. Fire-fighting activities that may result in potential exposure to high heat, smoke or toxic by-products of combustion should require NIOSH/MSHA- approved pressure-demand self-contained breathing apparatus with full facepiece and full protective clothing. Isolate area around container involved in fire. Cool tanks, shells, and containers exposed to fire and excessive heat with water. For massive fires the use of unmanned hose holders or monitor nozzles may be advantageous to further minimize personnel exposure. Major fires may require withdrawal, allowing the tank to burn.

Hazardous combustion products

Carbon monoxide, carbon dioxide and non-combusted hydrocarbons (smoke).

Further information

Dispose of fire debris and contaminated extinguishing water in accordance with official regulations.

6. ACCIDENTAL RELEASE MEASURES**Emergency measures**

Evacuate nonessential personnel and remove or secure all ignition sources. Ventilate the area. Consider wind direction; stay upwind and uphill, if possible. Evaluate the direction of product travel, diking, sewers, etc. to confirm spill areas. Spills may infiltrate subsurface soil and groundwater; professional assistance may be necessary to determine the extent of subsurface impact.

Personal precautions and protective equipment

Response and clean-up crews must be properly trained and must utilize proper protective equipment (see Section 8).

QUICSEAL CONSTRUCTION CHEMICALS PTE LTD

No. 7 Eunos Avenue 8A Eunos Industrial Estate Singapore 409460 Tel: (65) 6742 4466 Fax: (65) 6741 4666

Website: www.quicseal.com Co.Reg. No.: 198201286W



Environmental precautions

Protect bodies of water by diking, absorbents, or absorbent boom, if possible. Do not flush down sewer or drainage systems, unless system is designed and permitted to handle such material. The use of fire fighting foam may be useful in certain situations to reduce vapors. The proper use of water spray may effectively disperse product vapors or the liquid itself, preventing contact with ignition sources or areas/equipment that require protection.

Methods and materials for containment and cleaning up

Carefully contain and stop the source of the spill, if safe to do so. Collect spillages by means of spark proof equipment. Use water only to remove residuals, so as not to run the risk of entering the sewer. Do not let the product dry. Contaminated clothes must be left to soak in water before washing.

Spillage in waters: remove the liquid from the surface with flameproof pumps or manual pumps or suitable absorbent material. Resort to sinking and/or dispersion of the product with suitable substances in open waters, if permitted by the law.

7. HANDLING AND STORAGE**Precautions for safe handling**

Handle as a combustible liquid Do not smoke, use matches or lighters. Keep the containers earthed while decanting and wear antistatic boots. Vigorous stirring and flow through the piping and equipment may cause the formation and accumulation of electrostatic charges due to the low conductivity of the product. In order to avoid the risk of fire outbreak and explosion never use compressed air during movement. Bond and ground containers during product transfer to reduce the possibility of static-initiated fire or explosion.

Conditions for safe storage, including any incompatibilities

Avoid the accumulation of electrostatic charges. Store the containers sealed in a cool and ventilated place, never at extreme temperatures. and in a well-ventilated place. Keep out of the reach of children. Don't overload shelves or tables with tins of the product. Vapours may ignite with explosion, it is therefore necessary to avoid accumulation keeping the windows and doors open, ensuring cross ventilation. Without adequate ventilation, the vapours may accumulate at the bottom and ignite at a distance, if triggered off with the risk of flashback. Keep far away from sources of heat, sparks and naked flames. Always keep the labelling in sight because it lists the potential risks. Keep containers closed and clearly labelled. Empty product containers or vessels may contain explosive vapors. Do not pressurize, cut, heat, weld or expose such containers to sources of ignition. Avoid storage near incompatible materials. Keep away from strong oxidizers.

8. EXPOSURE CONTROLS AND PERSONAL PROTECTION**Control Parameters / Occupational Exposure Limits**

COMPONENTS	CAS No.	Singapore Permissible Exposure Limit	
		Short-Term	Long-Term
Ethyl Acetate	141-78-6	--	400 ppm / 1,440 mg/m ³
2-Propanol	67-63-0	500 ppm / 1,230 mg/m ³	400 ppm / 983 mg/m ³
Solvent Naphtha (Petroleum) Medium	64742-88-7	--	1,700 mg/m ³

QUICSEAL CONSTRUCTION CHEMICALS PTE LTD

No. 7 Eunos Avenue 8A Eunos Industrial Estate Singapore 409460 Tel: (65) 6742 4466 Fax: (65) 6741 4666

Website: www.quicseal.com Co.Reg. No.: 198201286W



Appropriate engineering measure

Use adequate ventilation to keep vapor concentrations of this product below occupational exposure and flammability limits, particularly in confined spaces.

Personal protective equipmentHand Protection

Solvent-proof gloves constructed of nitrile, neoprene, or PVC are recommended.

Eye Protection

Safety glasses or goggles are recommended where there is a possibility of splashing or spraying.

Skin Protection

Chemical protective clothing such as of E.I. DuPont TyChem®, Saranex® or equivalent recommended based on degree of exposure.

Respiratory Protection

A NIOSH/MSHA-approved air-purifying respirator with organic vapor cartridges or canister may be permissible under certain circumstances where airborne concentrations are or may be expected to exceed exposure limits or for odor or irritation. Protection provided by air-purifying respirators is limited.

Use a positive pressure, air-supplied respirator if there is a potential for uncontrolled release, exposure levels are not known, in oxygen-deficient atmospheres, or any other circumstance where an air-purifying respirator may not provide adequate protection.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state:	Transparent Liquid
Odour:	Stinging
Flash Point:	24°C (referring to pure solvents mixture)
Initial boiling point / range:	Not available
Autoignition temperature:	Not available
Flammability Limits (vol%):	Not available
Vapor pressure (20°C):	Not available
Water Solubility (25°C):	Immiscible
Specific Gravity:	Approx. 0.83

10. STABILITY AND REACTIVITY**Chemical stability**

The product is flammable. The liquid and vapour is readily combustible.

Possibility of hazardous reactions

This product reacts violently with strong oxidizing agents. Concentrated vapours may form explosive mixtures with the air.

QUICSEAL CONSTRUCTION CHEMICALS PTE LTD

No. 7 Eunos Avenue 8A Eunos Industrial Estate Singapore 409460 Tel: (65) 6742 4466 Fax: (65) 6741 4666

Website: www.quicseal.com Co.Reg. No.: 198201286W



Conditions to avoid

Avoid high temperatures, open flames, sparks, welding, smoking & other ignition sources.

Incompatible materials

Keep away from strong oxidizers and strong acids.

Hazardous decomposition products

Carbon monoxide, carbon dioxide and non-combusted hydrocarbons (smoke).

11. TOXICOLOGICAL INFORMATION

This product has not been tested and all the toxicological statements have been derived from the respective components' available toxicity information.

Acute toxicity

Experimental/calculated data:

LD50 (rat), oral: > 5,000 mg/kg (the product is not harmful if swallowed.)

LD50 (rabbit), dermal: > 5,000 mg/kg (the product is not harmful in contact with skin)

LC50 (4 hr exposure): > 20 mg/L (the product is not harmful if inhaled)

Skin and Eye Irritation

The product causes serious eye irritation due to the following components:

Ethyl Acetate, CAS No.: 141-78-6 – Eye irritant (Category 2)

2-Propanol, CAS No.: 67-63-0 – Eye irritant (Category 2)

Solvent Naphtha (Petroleum) Medium, CAS No.: 64742-88-7 – Eye irritant (Category 2)

Respiratory / Skin sensitization

The product is not expected to cause respiratory or skin sensitization.

Germ cell mutagenicity / Carcinogenicity / Reproductive toxicity / Developmental toxicity

Based on the assessment of available information, the product is: not mutagenic in bacteria; has no known carcinogenic effect; and not expected to cause reproductive and developmental toxicity.

Specific target organ toxicity (single and repeated exposure)

Based on the available information, this product may cause drowsiness or dizziness on single exposure. The product is not expected to cause damage to any organs on prolonged or repeated exposure.

12. ECOLOGICAL INFORMATION

The following ecological assessment is based on the available ecotoxicity information of the product's components.

Ecotoxicity

This product is not expected to be toxic to aquatic life based on the toxicity values to the following aquatic organisms:

Fish: LC50 (96h) > 100 mg/l, *Brachydanio rerio* (OECD Guideline 203, static)

Aquatic invertebrates: EC50 (48h) > 100 mg/l, *Daphnia magna* (OECD Guideline 202, part 1, static)

Aquatic plants: LC50 (72h) > 100 mg/l, *Scenedesmus subspicatus* (OECD Guideline 201)

QUICSEAL CONSTRUCTION CHEMICALS PTE LTD

No. 7 Eunos Avenue 8A Eunos Industrial Estate Singapore 409460 Tel: (65) 6742 4466 Fax: (65) 6741 4666

Website: www.quicseal.com Co.Reg. No.: 198201286W



Additional information

Do not release product untreated into natural waters. At the present knowledge of the product, no negative ecological effects are expected.

13. DISPOSAL CONSIDERATIONS**Description of waste residues and information on their safe handling & methods of disposal**

Dispose of the product through licensed hazardous waste collectors under Singapore regulations. Provide the hazardous waste collector the sufficient information on the various hazards of this product.

Disposal of any contaminated packaging

Dried material can be disposed off in authorized landfill site in accordance to national regulations. Container should be recycled after cleaning or dispose of the container through licensed hazardous waste collectors under Singapore regulations. Provide the hazardous waste collector the sufficient information on the various hazards of this product in this container.

14. TRANSPORT INFORMATION**Land Transport (ADR/RID):**

Shipping Name: RESIN SOLUTION
 UN #: 1866
 Hazard Class: 3
 Label: 3
 Nr. Kemler: 30
 Packing Group: III
 Packaging Instructions: 640D

Label:

**Air Transport (IATA/CAO):**

Shipping Name: RESIN SOLUTION
 UN #: 1866
 Hazard Class: 3
 Label: 3
 Packing Group: III
 Cargo Packaging Instructions: 307 (Max. Quantity: 60L)
 Passenger Packaging Instructions: 305 (Max. Quantity: 5L)

Label:

**Sea transport (IMDG):**

Shipping Name: RESIN SOLUTION
 UN #: 1866
 Hazard Class: 3
 Packing Group: III
 EmS Number: F-E S-E
 Marine pollutant: No

Label:

**QUICSEAL CONSTRUCTION CHEMICALS PTE LTD**

No. 7 Eunos Avenue 8A Eunos Industrial Estate Singapore 409460 Tel: (65) 6742 4466 Fax: (65) 6741 4666

Website: www.quicseal.com Co.Reg. No.: 198201286W



15. REGULATORY INFORMATION

Applicable National Regulations

This product is subject to the requirements in the following acts/regulations:

Workplace Safety and Health Act & Workplace Safety and Health (General Provisions) Regulations
Environmental Protection and Management Act and Environmental Protection and Management
Maritime and Port Authority of Singapore (Dangerous Goods, Petroleum and Explosives)

International Regulations

This product is classified as hazardous pursuant to the provision set forth in Directives 67/548/EEC and 1999/45/EC and/or EC Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of EC Regulation 1907/2006 and subsequent amendments.

16. OTHER INFORMATION

The information and data contained herein are believed to be accurate and reliable; however, it is the user's responsibility to determine suitability of use. Since QUICSEAL Construction Chemicals Pte. Ltd. cannot know all of the uses to which its products may be put or the conditions of use; it makes no warranties concerning the fitness or suitability of its products for a particular use of purpose.

QUICSEAL CONSTRUCTION CHEMICALS PTE LTD

No. 7 Eunos Avenue 8A Eunos Industrial Estate Singapore 409460 Tel: (65) 6742 4466 Fax: (65) 6741 4666

Website: www.quicseal.com Co.Reg. No.: 198201286W

