



**SAFETY DATA SHEET
QUICSEAL 717
LAP CEMENT**

1. INFORMATION OF THE SUBSTANCE/COMPOUND AND THE SUPPLIER

Product Name: QUICSEAL 717 – Multi-Purpose Lap Cement
Product Use: Sealing agent

Details of the supplier:

*QUICSEAL CONSTRUCTION CHEMICALS PTE LTD
No. 7 Eunos Avenue 8A
Eunos Industrial Estate
Singapore 409460*

Emergency Contact No.: (65) 6742 4466

2. HAZARDS IDENTIFICATION

GHS Classification:

Flammable liquid - Category 3
Aspiration hazard - Category 1
Chronic aquatic toxicity - Category 2

GHS LABEL ELEMENTS

Symbol(s):



Signal Word

Danger

Hazard Statements:

H226: Flammable liquid and vapour.
H304: May be fatal if swallowed and enters airways.
H411: Toxic to aquatic life with long lasting effects.

Precautionary Statements:

Prevention

P210: Keep away from heat/sparks/open flames/hot surfaces. No smoking
P233: Keep container tightly closed.
P240: Ground/bond container and receiving equipment.
P241: Use explosion-proof electrical/ventilating/lighting equipment.
P242: Use only non-sparking tools.
P243: Take precautionary measures against static discharge.
P273: Avoid release to the environment.
P280: Wear protective gloves/protective clothing/eye protection/face protection.

QUICSEAL CONSTRUCTION CHEMICALS PTE LTD

No. 7 Eunos Avenue 8A Eunos Industrial Estate Singapore 409460 Tel: (65) 6742 4466 Fax: (65) 6741 4666

Website: www.quicseal.com Co.Reg. No.: 198201286W



Response

P301+P310: IF SWALLOWED: Immediately call a POISON CENTER or doctor.

P303+P361+P353: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P331: Do NOT induce vomiting.

Storage

P403+P235: Store in a well ventilated place. Keep cool..

P405: Store locked up.

Disposal

P501: Dispose of contents/container in accordance with local/national regulations.

3. COMPOSITION / INFORMATION ON INGREDIENTS

This product contains the following components classified as hazardous:

COMPONENTS	CAS No.	EINECS No.	Index No.	Percentage
Turpentine	8006-64-2	232-350-7	650-002-00-6	Undisclosed
Bitumen	Undisclosed	--	--	Undisclosed

4. FIRST-AID MEASURES**General information**

Take person to a safe place. Observe self-protection for first aid. Always seek medical advice in the event of contact with this substance.

Inhalation

Keep the patient calm. If unconscious place in stable sideways position. Protect against loss of body heat. If breathing stops, administer artificial respiration. Seek medical advice immediately and clearly identify substance.

Skin contact

Remove contaminated clothes at once. Wash off with plenty of water or water and soap immediately for 10-15 minutes. In serious cases, use emergency shower immediately. Seek medical advice immediately and clearly identify substance.

Eye contact

Rinse immediately with plenty of water for 10-15 minutes. Keep eyelids well open to rinse the whole eye surface and eyelids with water. Seek medical advice immediately and clearly identify substance. Continue to bathe eyes during transport to medical practitioner.

Ingestion

If conscious, give several small portions of water to drink. Do not induce vomiting. Seek medical advice immediately and clearly identify substance.

QUICSEAL CONSTRUCTION CHEMICALS PTE LTD

No. 7 Eunos Avenue 8A Eunos Industrial Estate Singapore 409460 Tel: (65) 6742 4466 Fax: (65) 6741 4666

Website: www.quicseal.com Co.Reg. No.: 198201286W



Most important symptoms and effects, both acute and delayed

Irritation to eyes, skin, upper respiratory system; headache, drowsiness, dizziness, nausea, vomiting, visual disturbance..

5. FIRE-FIGHTING MEASURES**General Fire Hazards**

This product is classified as a FLAMMABLE LIQUID. See Section 9 for Flammability Properties.

Vapors may be ignited rapidly when exposed to heat, spark, open flame or other source of ignition. When mixed with air and exposed to an ignition source, flammable vapors can burn in the open or explode in confined spaces. Being heavier than air, vapors may travel long distances to an ignition source and flash back. Runoff to sewer may cause fire or explosion hazard.

Suitable Fire-extinguishing Media

SMALL FIRES: Any extinguisher suitable for Class B fires, dry chemical, CO₂, water spray, fire fighting foam, and other gaseous agents.

LARGE FIRES: Water spray, fog or fire fighting foam. Water may be ineffective for fighting the fire, but may be used to cool fire-exposed containers.

Fire-fighting Equipment / Instructions

Small fires in the incipient (beginning) stage may typically be extinguished using handheld portable fire extinguishers and other fire fighting equipment. Fire-fighting activities that may result in potential exposure to high heat, smoke or toxic by-products of combustion should require NIOSH/MSHA- approved pressure-demand self-contained breathing apparatus with full facepiece and full protective clothing. Isolate area around container involved in fire. Cool tanks, shells, and containers exposed to fire and excessive heat with water. For massive fires the use of unmanned hose holders or monitor nozzles may be advantageous to further minimize personnel exposure. Major fires may require withdrawal, allowing the tank to burn. Large storage tank fires typically require specially trained personnel and equipment to extinguish the fire, often including the need for properly applied fire fighting foam.

Hazardous Combustion Products

Carbon monoxide, carbon dioxide and non-combusted hydrocarbons (smoke).

Further information

Dispose of fire debris and contaminated extinguishing water in accordance with official regulations.

6. ACCIDENTAL RELEASE MEASURES**Emergency Measures**

Evacuate nonessential personnel and remove or secure all ignition sources. Consider wind direction; stay upwind and uphill, if possible. Evaluate the direction of product travel, diking, sewers, etc. to confirm spill areas. Spills may infiltrate subsurface soil and groundwater; professional assistance may be necessary to determine the extent of subsurface impact.

QUICSEAL CONSTRUCTION CHEMICALS PTE LTD

No. 7 Eunos Avenue 8A Eunos Industrial Estate Singapore 409460 Tel: (65) 6742 4466 Fax: (65) 6741 4666

Website: www.quicseal.com Co.Reg. No.: 198201286W



Personal Precautions and Protective equipment

Response and clean-up crews must be properly trained and must utilize proper protective equipment (see Section 8).

Environmental Precautions

Protect bodies of water by diking, absorbents, or absorbent boom, if possible. Do not flush down sewer or drainage systems, unless system is designed and permitted to handle such material. The use of fire fighting foam may be useful in certain situations to reduce vapors. The proper use of water spray may effectively disperse product vapors or the liquid itself, preventing contact with ignition sources or areas/equipment that require protection.

Methods and materials for containment and cleaning up

Carefully contain and stop the source of the spill, if safe to do so.

Take up with sand or other oil absorbing materials. Carefully shovel, scoop or sweep up into a waste container for reclamation or disposal. Caution, flammable vapors may accumulate in closed containers.

7. HANDLING AND STORAGE**Precautions for Safe Handling**

Avoid contact with skin and eyes. Avoid inhalation of vapour or mist.

Handle as a combustible liquid. Keep away from heat, sparks, excessive temperatures and open flame! No smoking or open flame in storage, use or handling areas. Bond and ground containers during product transfer to reduce the possibility of static-initiated fire or explosion.

Conditions for safe storage, including any incompatibilities

Store in a cool place. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Keep away from strong oxidizing agents such as halogens and concentrated nitric acid.

8. EXPOSURE CONTROLS AND PERSONAL PROTECTION**Control Parameters / Occupational Exposure Limits**

For component: Turpentine, CAS No.: 8006-64-2

Singapore Permissible Exposure Level (PEL), Long term: 100 ppm / 566 mg/m³

Engineering Measures

Use adequate ventilation to keep vapor concentrations of this product below occupational exposure and flammability limits, particularly in confined spaces.

Personal Protective Equipment:Hand Protection

Gloves constructed of nitrile, neoprene, or PVC are recommended.

The following should be considered when choosing work glove material: degradation, breakage times and permeation. Work glove resistance to preparations should be checked before use, as it can be unpredictable. Gloves' limit depends on the duration of exposure.

QUICSEAL CONSTRUCTION CHEMICALS PTE LTD

No. 7 Eunos Avenue 8A Eunos Industrial Estate Singapore 409460 Tel: (65) 6742 4466 Fax: (65) 6741 4666

Website: www.quicseal.com Co.Reg. No.: 198201286W



Eye Protection

Safety glasses or goggles are recommended where there is a possibility of splashing or spraying.

Skin Protection

Chemical protective clothing such as of E.I. DuPont TyChem®, Saranex® or equivalent recommended based on degree of exposure. Note: The resistance of specific material may vary from product to product as well as with degree of exposure. Consult manufacturer specifications for further information.

Respiratory Protection

A NIOSH/MSHA-approved air-purifying respirator with organic vapor cartridges or canister may be permissible under certain circumstances where airborne concentrations are or may be expected to exceed exposure limits or for odor or irritation. Protection provided by air-purifying respirators is limited.

Use a positive pressure, air-supplied respirator if there is a potential for uncontrolled release, exposure levels are not known, in oxygen-deficient atmospheres, or any other circumstance where an air-purifying respirator may not provide adequate protection.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state:	Dark liquid paste
Odour:	Hydrocarbon solvent odour
Flash point:	45°C
Boiling point:	155°C
Melting point:	Not available
Ignition temperature:	Not available
Flammability Limits:	0.7% – 6.5% vol%
Water Solubility:	Immiscible with water
Density:	1.112 g/cm ³

10. STABILITY AND REACTIVITY

Chemical stability

The product is flammable. The liquid and vapour is readily combustible. The product may soften oil or acrylic coatings.

Possibility of hazardous reactions

This product reacts with strong oxidizing agents such as halogens and concentrated nitric acid.

Conditions to avoid

Avoid high temperatures, open flames, sparks, welding, smoking and other ignition sources.

Incompatible materials

Keep away from strong oxidizers.

Hazardous decomposition products

Carbon monoxide, carbon dioxide and non-combusted hydrocarbons (smoke).

QUICSEAL CONSTRUCTION CHEMICALS PTE LTD

No. 7 Eunos Avenue 8A Eunos Industrial Estate Singapore 409460 Tel: (65) 6742 4466 Fax: (65) 6741 4666

Website: www.quicseal.com Co.Reg. No.: 198201286W



11. TOXICOLOGICAL INFORMATION

This product has not been tested and all the toxicological statements have been derived from the respective components' available toxicity information.

Acute toxicity

Experimental/calculated Acute Toxicity Estimates (ATE):

LD50, oral: ~500 mg/kg (the product is harmful if swallowed.)

LD50, dermal: ~1,100 mg/kg (the product is harmful in contact with skin)

LC50, inhalation: ~11 mg/L (the product is harmful if inhaled)

This product is harmful if swallowed, inhaled, and in contact with skin.

Skin and Eye Irritation

This product contains the following component classified as skin and eye irritant:

Turpentine, CAS No.: 8006-64-2: Skin and eye irritant based on relevant animal tests.

Respiratory / Skin sensitization

This product may cause an allergic skin reaction. It is not expected to cause respiratory sensitization.

Aspiration hazard

This product may be harmful if swallowed and enters airways.

Germ cell mutagenicity / Carcinogenicity / Reproductive toxicity / Developmental toxicity

Based on the assessment of available information, the product is: not mutagenic in bacteria; has no known carcinogenic effect; and not expected to cause reproductive and developmental toxicity.

Specific target organ toxicity (single and repeated exposure)

Based on the available information, there is no specific target organ toxicity expected after a single or repeated exposure to the product.

12. ECOLOGICAL INFORMATION

The following ecological assessment is based on the available ecotoxicity information of the product's main components.

Chronic toxicity to the aquatic environment

Estimated LC values based on component's toxicity to fish: LC50 (96h): 1-10 mg/L

The product is not rapidly degradable with an estimated $\log K_{ow} \geq 4$.

This product is toxic to aquatic life with long lasting effects (Chronic toxicity to the aquatic environment Category 2)

QUICSEAL CONSTRUCTION CHEMICALS PTE LTD

No. 7 Eunos Avenue 8A Eunos Industrial Estate Singapore 409460 Tel: (65) 6742 4466 Fax: (65) 6741 4666

Website: www.quicseal.com Co.Reg. No.: 198201286W



13. DISPOSAL CONSIDERATIONS

Description of waste residues and information on their safe handling & methods of disposal

Dispose of the product through licensed hazardous waste collectors under Singapore regulations. Provide the hazardous waste collector the sufficient information on the various hazards of this product.

Disposal of any contaminated packaging

Dried material can be disposed off in authorized landfill site in accordance to national regulations. Container should be recycled after cleaning or dispose of the container through licensed hazardous waste collectors under Singapore regulations. Provide the hazardous waste collector the sufficient information on the various hazards of this product in this container.

14. TRANSPORT INFORMATION

Land Transport (ADG)

Shipping Name: TURPENTINE
UN #: 1299
Hazard Class: 3
Packing Group: III

Label:



Air Transport (IATA)

Shipping Name: TURPENTINE
UN #: 1299
Class: 3
Packaging group: III

Label:



Sea transport (IMDG)

Shipping Name: TURPENTINE
UN #: 1299
Class: 3
Packaging group: III
EmS Number: F-,E S-E
Marine pollutant: No

Label:



15. REGULATORY INFORMATION

Applicable National Regulations

This product is subject to the requirements in the following acts/regulations:

Workplace Safety and Health Act & Workplace Safety and Health (General Provisions) Regulations
Environmental Protection and Management Act and Environmental Protection and Management
Maritime and Port Authority of Singapore (Dangerous Goods, Petroleum and Explosives)

QUICSEAL CONSTRUCTION CHEMICALS PTE LTD

No. 7 Eunos Avenue 8A Eunos Industrial Estate Singapore 409460 Tel: (65) 6742 4466 Fax: (65) 6741 4666

Website: www.quicseal.com Co.Reg. No.: 198201286W



International Regulations

This product is classified as hazardous pursuant to the provision set forth in Directives 67/548/EEC and 1999/45/EC and/or EC Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of EC Regulation 1907/2006 and subsequent amendments.

16. OTHER INFORMATION

The information and data contained herein are believed to be accurate and reliable; however, it is the user's responsibility to determine suitability of use. Since QUICSEAL Construction Chemicals Pte. Ltd. cannot know all of the uses to which its products may be put or the conditions of use; it makes no warranties concerning the fitness or suitability of its products for a particular use of purpose.

QUICSEAL CONSTRUCTION CHEMICALS PTE LTD

No. 7 Eunos Avenue 8A Eunos Industrial Estate Singapore 409460 Tel: (65) 6742 4466 Fax: (65) 6741 4666

Website: www.quicseal.com Co.Reg. No.: 198201286W

