



# BluSeal VLDPE Tunnel Liner

VLDPE FLEXIBLE SHEET MEMBRANE



BluSeal VLDPE Tunnel Liner is an extruded very low density polymer polyethylene sheet which requires only installation and welding to form a flexible and durable tunnel membrane.

## Uses

BluSeal VLDPE Tunnel Liner is used for lining bored and driven tunnels, cut and cover tunnels, cross passages, shafts and underground structures. BluSeal VLDPE Tunnel Liner comes in a range of thicknesses for various performance applications. The membrane is applied to structures to prevent water inflow and provide asset protection.

## Advantages

- Flexibility to conform to various surface profiles
- High tear strength and elongation
- Exceptional waterproofing performance
- Long term durability
- Good weldability

## Advantages

Shotcrete and rock surfaces must be smooth and free of sharp edges. Generally, changes in direction and voids must be limited to less than 10% over any measured length. For example, over a 1m length no void or protrusion should exceed 100mm. Fibre reinforced shotcrete must be covered with a smoothing layer and generally aggregate sizes greater than 10mm should be avoided. Membrane must be placed over non-woven geotextile not less than 500g/m<sup>2</sup> in weight.

## Advantages

BluSeal VLDPE Tunnel Liner must be installed by an approved, specialised applicator. Experience in installation techniques and testing is essential. The membrane shall be fixed using compatible roundels supplied by Bluey. Following installation of geotextile, the roundels are nailed to the surface using suitable nail gun. Roundels shall be set in a pattern to adequately support the membrane, this will vary between the tunnel crown, walls and invert. BluSeal VLDPE Tunnel Liner is then heat welded to the roundels in a manner which will allow the connection to break under load without causing damage to the membrane. The BluSeal VLDPE Tunnel Liner shall be hung to the roundels with adequate 'quilting' to prevent stress during concrete placement. Excessive 'quilting' must also be avoided to prevent folds in the membrane. Seams shall be welded by a hot wedge double seam in accordance with DVS 2227. Each seam shall be tested in accordance with DVS 2227 or equivalent local standards.



# BluSeal VLDPE Tunnel Liner

## VLDPE FLEXIBLE SHEET MEMBRANE

### Product Data

Please refer to Important Notice on following page

<b>Packaging</b>	Various widths, lengths and thicknesses available
<b>Behaviour @ 80°C</b>	Dimensionally stable <2% Change of tensile strength <20% Change of % elongation <20%
<b>Density</b>	≥900kg/m <sup>3</sup>

TESTED CHARACTERISTIC	STANDARD	RESULT
Material Consistency	DIN 16726	≤50mm Straightness - complies ≤10mm Flatness - complies
Tensile Strength	DIN 16726	≤15MPa
Elongation @ Break	DIN EN ISO 527	≥500% along/across
Puncture Resistance	DIN 16726	Complies 750mm drop test
Fire Resistance	DIN 4102	B2
Multiaxial Tension	DIN 53861 - Dia 1m	>50%
Melt Flow Rate	DIN EN ISO 1133/4	0.7 - 1.3g/10min



# BluSeal VLDPE Tunnel Liner

## VLDPE FLEXIBLE SHEET MEMBRANE

### Contact Bluey

#### BRISBANE (HEAD OFFICE)

Bluey Technologies Pty Ltd  
Unit 8, 53 Metroplex Avenue, Murarrie Qld 4172 Australia  
Ph +61 7 3399 3635 Fax +61 7 3899 9822 brisbane@bluey.com.au

#### SYDNEY

Bluey Technologies Pty Ltd  
Unit 3, 35 Higginbotham Road, Gladesville NSW 2111 Australia  
Ph +61 2 9807 2207 sydney@bluey.com.au

#### MELBOURNE

Bluey Technologies Pty Ltd  
PO Box 170, Tullamarine VIC 3043 Australia  
Ph +61 3 9826 5570 melbourne@bluey.com.au

#### PERTH

Bluey Technologies Pty Ltd  
Ph +61 402 372 308 perth@bluey.com.au

#### AUCKLAND

Bluey Technologies  
Ph +64 21 102 4797 nz@bluey.com.au

[www.bluey.com.au](http://www.bluey.com.au)

#### BLUEY ASIA PACIFIC DISTRIBUTOR

##### QUICSEAL CONSTRUCTION CHEMICALS PTE LTD

No.7 Eunos Avenue 8A, Eunos Industrial Estate, (S)409460 Singapore  
Ph +65 6742 4466 Fax +65 6741 4666

[www.quicseal.com](http://www.quicseal.com)

#### IMPORTANT NOTICE

This Technical Data Sheet is provided for general information and instruction only. Bluey does not warrant that the information it contains is accurate, reliable or complete. Bluey does not warrant that the product (or any related services) will achieve any of the characteristics set out herein in any particular application in the field, nor that it will be suitable for any specific use or purpose. The properties and characteristics set out herein represent typical testing results under laboratory conditions only. Results of actual product implementation may vary. Site-specific and project-specific criteria will affect product performance, including without limitation: surfaces, materials or products used with the product or to which the product is applied; and weather, climatic or seasonal conditions. The user must take into account all such criteria relevant to the project concerned when considering any desired results, including by undertaking trial mixing and application under site conditions. Not all product parameters are batch tested as part of the manufacturing quality control process, and performance may vary between batches.

If Bluey gives any express written product warranty in relation to the product, that warranty is subject to the foregoing qualifications, despite anything to the contrary in any other document. All other representations, advice, suggestions or promises regarding the product's performance or its implementation, whether verbal or in writing, and whenever given, including in the course of any field services, are expressly disclaimed. Without limiting the foregoing, Bluey will have no liability for loss or damage of any kind if any application specifications are not followed.

The foregoing is not intended to exclude any warranties or guarantees which by law cannot be excluded. Subject only to the foregoing provisions of this Notice, and to the extent permitted by law, Bluey disclaims all liability for loss or damage of any kind suffered as a result of or in connection with the product or its implementation. If such liability cannot be wholly excluded, Bluey's liability will, to the extent permitted by law, be limited to the replacement of the product itself or the direct cost of replacement of the product itself (not including any collateral or consequential loss or damage of any kind).

© Bluey Technologies Pty Ltd