



SAFETY DATA SHEET
QUICSEAL 200 – PART A
FUEL RESISTANT PITCH FREE CONCRETE PAVEMENT JOINT SEALANT

1. INFORMATION OF THE SUBSTANCE/COMPOUND AND THE SUPPLIER

Product Name: QUICSEAL 200 – Jet Fuel Resistant Sealant (Part A)
Product Use: Part A of a 2-component liquid pitch-free self-leveling elastomeric sealant

Details of the supplier:

QUICSEAL CONSTRUCTION CHEMICALS PTE LTD
No. 7 Eunos Avenue 8A
Eunos Industrial Estate
Singapore 409460

Emergency Contact No.: (65) 6742 4466

2. HAZARDS IDENTIFICATION

GHS Classification:

Skin Irritation - Category 2
Skin Irritation – Category 2

GHS LABEL ELEMENTS

Symbol(s):



Signal Word

Warning

Hazard Statements:

H315: Causes skin irritation.
H319: Causes serious eye irritation.

Precautionary Statements:

Prevention

P280: Wear protective gloves/protective clothing/ eye protection/ face protection.

Response

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes.
Remove contact lenses, if present and easy to do so.

P332+P313: If skin irritation occurs: Get medical advice/attention.

QUICSEAL CONSTRUCTION CHEMICALS PTE LTD

No. 7 Eunos Avenue 8A Eunos Industrial Estate Singapore 409460 Tel: (65) 6742 4466 Fax: (65) 6741 4666

Website: www.quicseal.com Co.Reg. No.: 198201286W



3. COMPOSITION / INFORMATION ON INGREDIENTS

This product contains the following components classified as hazardous:

COMPONENTS	CAS No.	GHS Symbols	Percentage
Limestone	1317-65-3	GHS07	50 – 75 %
Iron Oxide	1317-61-9	GHS02	1.0 – 2.5 %

4. FIRST-AID MEASURES

General information

Take person to a safe place. Observe self-protection for first aid. Always seek medical advice in the event of contact with this substance.

Inhalation

Keep the patient calm. If unconscious place in stable sideways position. Protect against loss of body heat. If breathing stops, administer artificial respiration. Seek medical advice immediately and clearly identify substance.

Skin contact

Remove contaminated clothes at once. Wash off with plenty of water or water and soap immediately for 10-15 minutes. In serious cases, use emergency shower immediately. Seek medical advice immediately and clearly identify substance.

Eye contact

Rinse immediately with plenty of water for 10-15 minutes. Keep eyelids well open to rinse the whole eye surface and eyelids with water. Seek medical advice immediately and clearly identify substance. Continue to bathe eyes during transport to medical practitioner.

Ingestion

If conscious, give several small portions of water to drink. Do not induce vomiting. Seek medical advice immediately and clearly identify substance.

QUICSEAL CONSTRUCTION CHEMICALS PTE LTD

No. 7 Eunos Avenue 8A Eunos Industrial Estate Singapore 409460 Tel: (65) 6742 4466 Fax: (65) 6741 4666

Website: www.quicseal.com Co.Reg. No.: 198201286W



5. FIRE-FIGHTING MEASURES

General Fire Hazards

The product is non-flammable. If material is involved in fire, do not breathe fumes.

Suitable Fire-extinguishing Media

Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

Use the appropriate fire extinguishing media for surrounding fire (water, foam, dry powder, CO₂)

Hazardous Combustion Products

Carbon dioxide and carbon monoxide may be liberated during thermal decomposition.

Further information

Dispose of fire debris and contaminated extinguishing water in accordance with official regulations.

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions and Protective equipment and Emergency Measures

Use personal protective equipment. Avoid breathing vapours, mist or gas. Ensure adequate ventilation. Evacuate personnel to safe areas.

Environmental Precautions

Protect bodies of water by diking, absorbents, or absorbent boom, if possible. Do not flush down sewer or drainage systems, unless system is designed and permitted to handle such material.

Methods and materials for containment and cleaning up

Carefully contain and stop the source of the spill, if safe to do so. Take up with sand or other oil absorbing materials. Carefully shovel, scoop or sweep up into a waste container for reclamation or disposal.

7. HANDLING AND STORAGE

Precautions for safe handling

Handle in accordance to good industrial hygiene and safety practices (i.e. gloves, goggles, and safety equipment should be used when handling chemicals; do not eat, drink, smoke when handling product). Wash hand thoroughly before eating and drinking. Any accidental contact with the product must be washed with clean water.

Conditions for safe storage, including any incompatibilities

Store in a cool place. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

QUICSEAL CONSTRUCTION CHEMICALS PTE LTD

No. 7 Eunos Avenue 8A Eunos Industrial Estate Singapore 409460 Tel: (65) 6742 4466 Fax: (65) 6741 4666

Website: www.quicseal.com Co.Reg. No.: 198201286W



8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

Control Parameters / Occupational Exposure Limits

This product contains trace amounts of the following substance with relevant occupational exposure limits:

Coal tar pitch, CAS No. 65996-93-2: ACGIH2005, TLV-TWA = 0.2 mg/m³

Engineering Measures

Use adequate ventilation to keep vapor concentrations of this product below occupational exposure limits, particularly in confined spaces.

Personal Protective Equipment:

Eye/face protection

Safety glasses with side-shields conforming to EN166 Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

Skin protection

Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices.

Wash and dry hands. The selected protective gloves have to satisfy the specifications of EU Directive 89/686/EEC and the standard EN 374 derived from it.

Full contact: Material: Nitrile rubber / Min. layer thickness: 0.4 mm / Break-through time: 480 min.

Splash contact: Material: Nature latex/chloroprene / Min. layer thickness: 0.6 mm /
Break-through time: 60 min.

Body Protection

Impervious clothing, The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

Respiratory protection

Where risk assessment shows air-purifying respirators are appropriate use a full-face respirator with multi-purpose combination (US) or type ABEK (EN 14387) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

QUICSEAL CONSTRUCTION CHEMICALS PTE LTD

No. 7 Eunos Avenue 8A Eunos Industrial Estate Singapore 409460 Tel: (65) 6742 4466 Fax: (65) 6741 4666

Website: www.quicseal.com Co.Reg. No.: 198201286W



9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state:	Coloured Liquid
Odour:	Mild
Flash Point:	>247°C
Initial boiling point / range:	250°C
Freezing / Melting point:	Not available
Autoignition temperature:	Not available
Flammability Limits (vol%):	Not available
Vapor pressure (20°C):	Not available
Vapor density:	> 1
Water Solubility (25°C):	Not soluble
Specific Gravity:	Approx. 1.5

10. STABILITY AND REACTIVITY

Stability

The product is stable in normal conditions of use and storage. However, avoid extreme temperatures which can cause thermal decomposition.

Possibility of hazardous reactions

No hazardous reactions are foreseeable under normal conditions of use and storage.

Incompatible materials

Keep away from strong oxidizing agents and strong bases.

Hazardous decomposition products

No hazardous decomposition products are expected if stored and handled as prescribed/indicated. In cases of unavoidable circumstances (e.g. fire), thermal decomposition may yield carbon monoxide, carbon dioxide, nitrogen compounds, hydrogen chloride.

11. TOXICOLOGICAL INFORMATION

This product has not been tested and all the toxicological statements have been derived from the respective components' available toxicity information.

Acute toxicity

Experimental/calculated data:

LD50 (rat), oral: > 5,000 mg/kg (the product is not harmful if swallowed.)

LD50 (rabbit), dermal: > 5,000 mg/kg (the product is not harmful in contact with skin)

LC50 (4 hr exposure): > 20 mg/L (the product is not harmful if inhaled)

Skin and Eye Irritation

The product causes serious skin and eye irritation due to the following component:

Coal Tar, CAS No.: 8007-45-2 – Skin Irritant (Category 3) and Serious eye damage (Category 1)

QUICSEAL CONSTRUCTION CHEMICALS PTE LTD

No. 7 Eunos Avenue 8A Eunos Industrial Estate Singapore 409460 Tel: (65) 6742 4466 Fax: (65) 6741 4666

Website: www.quicseal.com Co.Reg. No.: 198201286W



Respiratory / Skin sensitization

The product is not expected to cause respiratory sensitization. There is a report that the component coal tar caused skin sensitization in humans. It was referred to as Category 1, since the hypersensitivity against light was also identified (IARC 35 (1985)).

Germ cell mutagenicity

Based on the available data for the component coal tar, test cases in humans (IARC (vol.35, 1985)) were the microbe mutagenicity tests which used the metabolic wastes in the body, and were not the in vivo tests. However, there was a mutagenicity positive finding for the somatic cells (ATSDR (2002)) and there was also positive in vitro finding, thus leading to the classification of the component into Category 2.

Carcinogenicity

The product component coal tar is a known human carcinogen (IARC: 1, ACGIH: A1, Occupational Health Society: 1st group).

Reproductive toxicity

The product component Butyl Benzyl Phthalate is a presumed human reproductive toxicant. Over-exposure may cause reproductive disorder(s) based on tests with laboratory animals.

Specific target organ toxicity - single exposure

The product component coal tar is classified into "Category 1 (nervous systems)" from statement with neurotoxin in humans (Patty (5th.2001)). And it is classified into "Category 3" (respiratory irritation) based on that the respiratory irritation is described to another literature (Patty (5th. 2001)).

Specific target organ toxicity - repeated exposure

The product component coal tar is classified into "Category 2" based on the report that the adverse effects appeared in the respiratory tract of the mouse by aerosols repeated exposure of 0.09 mg/L (within the guidance value range of Category 2) (IARC (vol.35 (1985))).

12. ECOLOGICAL INFORMATION

The following ecological assessment is based on the available ecotoxicity information of the product's components.

Toxicity to the aquatic environment

Component: Butyl Benzyl Phthalate

Toxicity to fish

LC50, *Lepomis macrochirus* (Bluegill) - 1.7 mg/l (96 h)

NOEC, *Oncorhynchus mykiss* (rainbow trout) - 0.48 mg/l (96 h, flow-through test)

LC50, *Pimephales promelas* (fathead minnow) - 2.1 mg/l (96 h, OECD Test Guideline 203)

Toxicity to daphnia and other aquatic invertebrates

LC50, *Daphnia magna* (Water flea) - 1.8 mg/l (48 h, static test)

Toxicity to algae

EC50, *Desmodesmus subspicatus* (green algae) - 0.31 mg/l (72 h, growth inhibition, OECD Test Guideline 20)

QUICSEAL CONSTRUCTION CHEMICALS PTE LTD

No. 7 Eunos Avenue 8A Eunos Industrial Estate Singapore 409460 Tel: (65) 6742 4466 Fax: (65) 6741 4666

Website: www.quicseal.com Co.Reg. No.: 198201286W



Persistence and degradability

Component: Butyl Benzyl Phthalate

Biodegradability aerobic - Exposure time 14 d
Result: 81 % - Readily biodegradable.**Bioaccumulative potential**

Component: Butyl Benzyl Phthalate

Bioaccumulation Lepomis macrochirus (Bluegill) - 21 d - 0.00973 mg/l
Bioconcentration factor (BCF): 663**Chronic toxicity to the aquatic environment**

This product is very toxic to aquatic life with long lasting effects. Avoid release to the environment.

13. DISPOSAL CONSIDERATIONS**Description of waste residues and information on their safe handling & methods of disposal**

Dispose of the product through licensed hazardous waste collectors under Singapore regulations. Provide the hazardous waste collector the sufficient information on the various hazards of this product.

Disposal of any contaminated packaging

Dried material can be disposed off in authorized landfill site in accordance to national regulations. Container should be recycled after cleaning or dispose of the container through licensed hazardous waste collectors under Singapore regulations. Provide the hazardous waste collector the sufficient information on the various hazards of this product in this container.

14. TRANSPORT INFORMATION**Land Transport (ADR/RID):**

Shipping Name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.

UN #: 3082

Hazard Class: 9

Packing Group: III

Air Transport (IATA/ICAO):

Shipping Name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.

UN #: 3082

Hazard Class: 9

Packing Group: III

Sea transport (IMDG):

Shipping Name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.

UN #: 3082

Hazard Class: 9

Packing Group: III

Marine pollutant: Yes

QUICSEAL CONSTRUCTION CHEMICALS PTE LTD

No. 7 Eunos Avenue 8A Eunos Industrial Estate Singapore 409460 Tel: (65) 6742 4466 Fax: (65) 6741 4666

Website: www.quicseal.com Co.Reg. No.: 198201286W

15. REGULATORY INFORMATION

Applicable National Regulations

This product is subject to the requirements in the following acts/regulations:

Workplace Safety and Health Act & Workplace Safety and Health (General Provisions) Regulations
Environmental Protection and Management Act and Environmental Protection and Management
Maritime and Port Authority of Singapore (Dangerous Goods, Petroleum and Explosives)

International Regulations

This product is classified as hazardous pursuant to the provision set forth in Directives 67/548/EEC and 1999/45/EC and/or EC Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of EC Regulation 1907/2006 and subsequent amendments.

16. OTHER INFORMATION

The information and data contained herein are believed to be accurate and reliable; however, it is the user's responsibility to determine suitability of use. Since QUICSEAL Construction Chemicals Pte. Ltd. cannot know all of the uses to which its products may be put or the conditions of use; it makes no warranties concerning the fitness or suitability of its products for a particular use of purpose.

QUICSEAL CONSTRUCTION CHEMICALS PTE LTD

No. 7 Eunos Avenue 8A Eunos Industrial Estate Singapore 409460 Tel: (65) 6742 4466 Fax: (65) 6741 4666

Website: www.quicseal.com Co.Reg. No.: 198201286W





SAFETY DATA SHEET
QUICSEAL 200 – PART B
FUEL RESISTANT PITCH FREE CONCRETE PAVEMENT JOINT SEALANT

1. INFORMATION OF THE SUBSTANCE/COMPOUND AND THE SUPPLIER

Product Name: QUICSEAL 200 – Fuel Resistant Sealant (Part B)
Product Use: Part B of a 2-component liquid pitch-free self-leveling elastomeric sealant

Details of the supplier:

QUICSEAL CONSTRUCTION CHEMICALS PTE LTD
No. 7 Eunos Avenue 8A
Eunos Industrial Estate
Singapore 409460

Emergency Contact No.: (65) 6742 4466

2. HAZARDS IDENTIFICATION

GHS Classification:

Flammable Liquid - Category 3
STOT, single exposure – Category 3
Chronic aquatic toxicity – Category 2

GHS LABEL ELEMENTS

Symbol(s):



Signal Word

Danger

Hazard Statements:

H226: Flammable liquid vapour
H335: May cause respiratory irritation
H411: Toxic to aquatic life with long lasting effects

QUICSEAL CONSTRUCTION CHEMICALS PTE LTD

No. 7 Eunos Avenue 8A Eunos Industrial Estate Singapore 409460 Tel: (65) 6742 4466 Fax: (65) 6741 4666

Website: www.quicseal.com Co.Reg. No.: 198201286W



Precautionary Statements:Prevention

P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources..

P261: Avoid breathing dust/fume/gas/mist/vapours/spray.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

Response

P304+P340: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

P391: Collect spillage.

Storage

P403+P233: Store in a well-ventilated place. Keep container tightly.

3. COMPOSITION / INFORMATION ON INGREDIENTS

This product contains the following components classified as hazardous:

COMPONENTS	CAS No.	GHS Symbols	Percentage
Solvent Naphtha (Petroleum)	64742-95-6	GHS02-GHS07-GHS08-GHS09	10 – 25 %
Mesitylene	108-67-8	GHS02-GHS07-GHS09	2.5 – 10 %

4. FIRST-AID MEASURES**General information**

Take person to a safe place. Observe self-protection for first aid. Always seek medical advice in the event of contact with this substance.

Inhalation

Keep the patient calm. If unconscious place in stable sideways position. Protect against loss of body heat. If breathing stops, administer artificial respiration. Seek medical advice immediately and clearly identify substance.

Skin contact

Remove contaminated clothes at once. Wash off with plenty of water or water and soap immediately for 10-15 minutes. In serious cases, use emergency shower immediately. Seek medical advice immediately and clearly identify substance.

Eye contact

Rinse immediately with plenty of water for 10-15 minutes. Keep eyelids well open to rinse the whole eye surface and eyelids with water. Seek medical advice immediately and clearly identify substance. Continue to bathe eyes during transport to medical practitioner.

Ingestion

If conscious, give several small portions of water to drink. Do not induce vomiting. Seek medical advice immediately and clearly identify substance.

QUICSEAL CONSTRUCTION CHEMICALS PTE LTD

No. 7 Eunos Avenue 8A Eunos Industrial Estate Singapore 409460 Tel: (65) 6742 4466 Fax: (65) 6741 4666

Website: www.quicseal.com Co.Reg. No.: 198201286W



5. FIRE-FIGHTING MEASURES

General Fire Hazards

The product is non-flammable. If material is involved in fire, do not breathe fumes.

Suitable Fire-extinguishing Media

Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

Use the appropriate fire extinguishing media for surrounding fire (water, foam, dry powder, CO₂)

Hazardous Combustion Products

Carbon dioxide and carbon monoxide may be liberated during thermal decomposition.

Further information

Dispose of fire debris and contaminated extinguishing water in accordance with official regulations.

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions and Protective equipment and Emergency Measures

Use personal protective equipment. Avoid breathing vapours, mist or gas. Ensure adequate ventilation. Evacuate personnel to safe areas.

Environmental Precautions

Protect bodies of water by diking, absorbents, or absorbent boom, if possible. Do not flush down sewer or drainage systems, unless system is designed and permitted to handle such material.

Methods and materials for containment and cleaning up

Carefully contain and stop the source of the spill, if safe to do so.

Take up with sand or other oil absorbing materials. Carefully shovel, scoop or sweep up into a waste container for reclamation or disposal.

7. HANDLING AND STORAGE

Precautions for safe handling

Handle in accordance to good industrial hygiene and safety practices (i.e. gloves, goggles, and safety equipment should be used when handling chemicals; do not eat, drink, smoke when handling product). Wash hand thoroughly before eating and drinking. Any accidental contact with the product must be washed with clean water.

Conditions for safe storage, including any incompatibilities

Store in cool place. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

QUICSEAL CONSTRUCTION CHEMICALS PTE LTD

No. 7 Eunos Avenue 8A Eunos Industrial Estate Singapore 409460 Tel: (65) 6742 4466 Fax: (65) 6741 4666

Website: www.quicseal.com Co.Reg. No.: 198201286W



8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

Control Parameters / Occupational Exposure Limits

This product contains trace amounts of the following substance with relevant occupational exposure limits:

Coal tar pitch, CAS No. 65996-93-2: ACGIH2005, TLV-TWA = 0.2 mg/m³

Engineering Measures

Use adequate ventilation to keep vapor concentrations of this product below occupational exposure limits, particularly in confined spaces.

Personal Protective Equipment:

Eye/face protection

Safety glasses with side-shields conforming to EN166 Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

Skin protection

Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands. The selected protective gloves have to satisfy the specifications of EU Directive 89/686/EEC and the standard EN 374 derived from it.

Full contact: Material: Nitrile rubber / Min. layer thickness: 0.4 mm / Break-through time: 480 min.

Splash contact: Material: Nature latex/chloroprene / Min. layer thickness: 0.6 mm /
Break-through time: 60 min.

Body Protection

Impervious clothing, The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

Respiratory protection

Where risk assessment shows air-purifying respirators are appropriate use a full-face respirator with multi-purpose combination (US) or type ABEK (EN 14387) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

QUICSEAL CONSTRUCTION CHEMICALS PTE LTD

No. 7 Eunos Avenue 8A Eunos Industrial Estate Singapore 409460 Tel: (65) 6742 4466 Fax: (65) 6741 4666

Website: www.quicseal.com Co.Reg. No.: 198201286W



9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state:	Clear, Amber
Odour:	Solvent
Flash Point:	38°C
Initial boiling point / range:	155 – 180°C
Freezing / Melting point:	Not available
Autoignition temperature:	Not available
Flammability Limits (vol%):	Not available
Vapor pressure (20°C):	Not available
VOC Content:	428
Water Solubility (25°C):	Not soluble
Specific Gravity:	0.975

10. STABILITY AND REACTIVITY

Stability

The product is stable in normal conditions of use and storage. However, avoid extreme temperatures which can cause thermal decomposition.

Possibility of hazardous reactions

No hazardous reactions are foreseeable under normal conditions of use and storage.

Incompatible materials

Keep away from strong oxidizing agents and strong bases.

Hazardous decomposition products

No hazardous decomposition products are expected if stored and handled as prescribed/indicated. In cases of unavoidable circumstances (e.g. fire), thermal decomposition may yield carbon monoxide, carbon dioxide, nitrogen compounds, hydrogen chloride.

11. TOXICOLOGICAL INFORMATION

This product has not been tested and all the toxicological statements have been derived from the respective components' available toxicity information.

Acute toxicity

Experimental/calculated data:

LD50 (rat), oral: > 5,000 mg/kg (the product is not harmful if swallowed.)

LD50 (rabbit), dermal: > 5,000 mg/kg (the product is not harmful in contact with skin)

LC50 (4 hr exposure): > 20 mg/L (the product is not harmful if inhaled)

Skin and Eye Irritation

The product causes serious skin and eye irritation due to the following component:

Coal Tar, CAS No.: 8007-45-2 – Skin Irritant (Category 3) and Serious eye damage (Category 1)

QUICSEAL CONSTRUCTION CHEMICALS PTE LTD

No. 7 Eunos Avenue 8A Eunos Industrial Estate Singapore 409460 Tel: (65) 6742 4466 Fax: (65) 6741 4666

Website: www.quicseal.com Co.Reg. No.: 198201286W



Respiratory / Skin sensitization

The product is not expected to cause respiratory sensitization. There is a report that the component coal tar caused skin sensitization in humans. It was referred to as Category 1, since the hypersensitivity against light was also identified (IARC 35 (1985)).

Germ cell mutagenicity

Based on the available data for the component coal tar, test cases in humans (IARC (vol.35, 1985)) were the microbe mutagenicity tests which used the metabolic wastes in the body, and were not the in vivo tests. However, there was a mutagenicity positive finding for the somatic cells (ATSDR (2002)) and there was also positive in vitro finding, thus leading to the classification of the component into Category 2.

Carcinogenicity

The product component coal tar is a known human carcinogen (IARC: 1, ACGIH: A1, Occupational Health Society: 1st group).

Reproductive toxicity

The product component Butyl Benzyl Phthalate is a presumed human reproductive toxicant. Over-exposure may cause reproductive disorder(s) based on tests with laboratory animals.

Specific target organ toxicity - single exposure

The product component coal tar is classified into "Category 1 (nervous systems)" from statement with neurotoxin in humans (Patty (5th.2001)). And it is classified into "Category 3" (respiratory irritation) based on that the respiratory irritation is described to another literature (Patty (5th. 2001)).

Specific target organ toxicity - repeated exposure

The product component coal tar is classified into "Category 2" based on the report that the adverse effects appeared in the respiratory tract of the mouse by aerosols repeated exposure of 0.09 mg/L (within the guidance value range of Category 2) (IARC (vol.35 (1985))).

12. ECOLOGICAL INFORMATION

The following ecological assessment is based on the available ecotoxicity information of the product's components.

Toxicity to the aquatic environment

Component: Butyl Benzyl Phthalate

Toxicity to fish

LC50, *Lepomis macrochirus* (Bluegill) - 1.7 mg/l (96 h)

NOEC, *Oncorhynchus mykiss* (rainbow trout) - 0.48 mg/l (96 h, flow-through test)

LC50, *Pimephales promelas* (fathead minnow) - 2.1 mg/l (96 h, OECD Test Guideline 203)

Toxicity to daphnia and other aquatic invertebrates

LC50, *Daphnia magna* (Water flea) - 1.8 mg/l (48 h, static test)

Toxicity to algae

EC50, *Desmodesmus subspicatus* (green algae) - 0.31 mg/l (72 h, growth inhibition, OECD Test Guideline 20)

QUICSEAL CONSTRUCTION CHEMICALS PTE LTD

No. 7 Eunos Avenue 8A Eunos Industrial Estate Singapore 409460 Tel: (65) 6742 4466 Fax: (65) 6741 4666

Website: www.quicseal.com Co.Reg. No.: 198201286W



Persistence and degradability

Component: Butyl Benzyl Phthalate

Biodegradability aerobic - Exposure time 14 d
Result: 81 % - Readily biodegradable.**Bioaccumulative potential**

Component: Butyl Benzyl Phthalate

Bioaccumulation Lepomis macrochirus (Bluegill) - 21 d - 0.00973 mg/l
Bioconcentration factor (BCF): 663**Chronic toxicity to the aquatic environment**

This product is very toxic to aquatic life with long lasting effects. Avoid release to the environment.

13. DISPOSAL CONSIDERATIONS**Description of waste residues and information on their safe handling & methods of disposal**

Dispose of the product through licensed hazardous waste collectors under Singapore regulations. Provide the hazardous waste collector the sufficient information on the various hazards of this product.

Disposal of any contaminated packaging

Dried material can be disposed off in authorized landfill site in accordance to national regulations. Container should be recycled after cleaning or dispose of the container through licensed hazardous waste collectors under Singapore regulations. Provide the hazardous waste collector the sufficient information on the various hazards of this product in this container.

14. TRANSPORT INFORMATION**Land Transport (ADR/RID):**

Shipping Name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.

UN #: 3082

Hazard Class: 9

Packing Group: III

Air Transport (IATA/ICAO):

Shipping Name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.

UN #: 3082

Hazard Class: 9

Packing Group: III

Sea transport (IMDG):

Shipping Name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.

UN #: 3082

Hazard Class: 9

Packing Group: III

Marine pollutant: Yes

QUICSEAL CONSTRUCTION CHEMICALS PTE LTD

No. 7 Eunos Avenue 8A Eunos Industrial Estate Singapore 409460 Tel: (65) 6742 4466 Fax: (65) 6741 4666

Website: www.quicseal.com Co.Reg. No.: 198201286W

15. REGULATORY INFORMATION

Applicable National Regulations

This product is subject to the requirements in the following acts/regulations:

Workplace Safety and Health Act & Workplace Safety and Health (General Provisions) Regulations
Environmental Protection and Management Act and Environmental Protection and Management
Maritime and Port Authority of Singapore (Dangerous Goods, Petroleum and Explosives)

International Regulations

This product is classified as hazardous pursuant to the provision set forth in Directives 67/548/EEC and 1999/45/EC and/or EC Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of EC Regulation 1907/2006 and subsequent amendments.

16. OTHER INFORMATION

The information and data contained herein are believed to be accurate and reliable; however, it is the user's responsibility to determine suitability of use. Since QUICSEAL Construction Chemicals Pte. Ltd. cannot know all of the uses to which its products may be put or the conditions of use; it makes no warranties concerning the fitness or suitability of its products for a particular use of purpose.

QUICSEAL CONSTRUCTION CHEMICALS PTE LTD

No. 7 Eunos Avenue 8A Eunos Industrial Estate Singapore 409460 Tel: (65) 6742 4466 Fax: (65) 6741 4666

Website: www.quicseal.com Co.Reg. No.: 198201286W

