



**SAFETY DATA SHEET**  
**QUICSEAL 201 Primer**  
**Single Component, Penetrating primer for concrete substrates**

**1. IDENTIFICATION OF THE SUBSTANCE/COMPOUND AND THE SUPPLIER**

Product Name: QUICSEAL 201 Primer  
Product Use: Priming of porous substrates (e.g. concrete and cementitious screeds)

Details of the supplier:

*QUICSEAL CONSTRUCTION CHEMICALS PTE LTD*  
*No. 7 Eunos Avenue 8A*  
*Eunos Industrial Estate*  
*Singapore 409460*

Emergency Contact No.: (65) 6742 4466

**2. HAZARDS IDENTIFICATION**

**GHS classification:**

Acute Toxicity Inhalation – Category 1  
Carcinogenicity – Category 2  
Flammable liquid – Category 3  
Reproductive toxicity – Category 1B  
Respiratory sensitization – Category 1

**GHS LABEL ELEMENTS**

**Symbol(s):**



**Signal Word**

Danger

**Hazard statements:**

H226: Flammable liquid and vapour  
H315: Causes skin irritation.  
H317: May cause an allergic skin reaction.  
H319: Causes serious eye irritation.  
H334: May cause allergy or asthma symptoms or breathing difficulties if inhaled.  
H335: May cause respiratory irritation.  
H351: Suspected of causing cancer.

**QUICSEAL CONSTRUCTION CHEMICALS PTE LTD**

No. 7 Eunos Avenue 8A Eunos Industrial Estate Singapore 409460 Tel: (65) 6742 4466 Fax: (65) 6741 4666

Website: [www.quicseal.com](http://www.quicseal.com) Co.Reg. No.: 198201286W



**Precautionary statements:**Prevention

- P201: Obtain special instructions before use.  
 P202: Do not handle until all safety precautions have been read and understood.  
 P210: Keep away from heat.  
 P233: Keep container tightly closed.  
 P260: Do not breathe mist/vapours/spray.  
 P270: Do not eat, drink or smoke when using this product.  
 P273: Avoid release to the environment.  
 P280: Wear protective gloves/protective clothing/eye protection/face protection.  
 P285: In case of inadequate ventilation, use respiratory protection.

Response

- P302+P352: IF ON SKIN: Wash with plenty of soap and water.  
 P304+P340: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.  
 P305+P351+P338: IN IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
 P308+P313: If exposed or concerned: Immediately call a POISON CENTER or doctor/physician.

Storage

- P403+P235: Store in a well ventilated place. Keep cool.

Disposal

- P501: Dispose of contents/container in accordance with national & international regulations.

**3. COMPOSITION / INFORMATION ON INGREDIENTS**

This product contains the following components classified as hazardous:

COMPONENTS	CAS No.	EINECS No.	Index No.
Toluylene Diisocyanate	26471-62-5	247-722-4	615-006-00-4
(1-Methoxy-2-propyl) Acetate	108-65-6	203-603-9	607-195-00-7

**QUICSEAL CONSTRUCTION CHEMICALS PTE LTD**

No. 7 Eunos Avenue 8A Eunos Industrial Estate Singapore 409460 Tel: (65) 6742 4466 Fax: (65) 6741 4666

Website: [www.quicseal.com](http://www.quicseal.com) Co.Reg. No.: 198201286W



#### 4. FIRST-AID MEASURES

##### General information

Take person to a safe place. Observe self-protection for first aid. Always seek medical advice in the event of contact with this substance.

##### Inhalation

Keep the patient calm. If unconscious place in stable sideways position. Protect against loss of body heat. If breathing stops, administer artificial respiration. Seek medical advice immediately and clearly identify substance.

##### Skin contact

Remove contaminated clothes at once. Wash off with plenty of water or water and soap immediately for 10-15 minutes. In serious cases, use emergency shower immediately. Seek medical advice immediately and clearly identify substance.

##### Eye contact

Rinse immediately with plenty of water for 10-15 minutes. Keep eyelids well open to rinse the whole eye surface and eyelids with water. Seek medical advice immediately and clearly identify substance. Continue to bathe eyes during transport to medical practitioner.

##### Ingestion

If conscious, give several small portions of water to drink. Do not induce vomiting. Seek medical advice immediately and clearly identify substance.

##### Notes to physician

Treat patient symptomatically (decontamination, vital functions).

#### 5. FIRE-FIGHTING MEASURES

##### General fire hazards

This product is classified as a FLAMMABLE LIQUID. See Section 9 for Flammability Properties.

Vapors may be ignited rapidly when exposed to heat, spark, open flame or other source of ignition. When mixed with air and exposed to an ignition source, flammable vapors can burn in the open or explode in confined spaces. Being heavier than air, vapors may travel long distances to an ignition source and flash back. Runoff to sewer may cause fire or explosion hazard.

##### Suitable Fire-extinguishing media

SMALL FIRES: Any extinguisher suitable for Class B fires, dry chemical, CO<sub>2</sub>, water spray, fire fighting foam, and other gaseous agents.

LARGE FIRES: Water spray, fog or fire fighting foam. Water may be ineffective for fighting the fire, but may be used to cool fire-exposed containers.

#### QUICSEAL CONSTRUCTION CHEMICALS PTE LTD

No. 7 Eunos Avenue 8A Eunos Industrial Estate Singapore 409460 Tel: (65) 6742 4466 Fax: (65) 6741 4666

Website: [www.quicseal.com](http://www.quicseal.com) Co.Reg. No.: 198201286W



**Fire-fighting equipment / instructions**

Small fires in the incipient (beginning) stage may typically be extinguished using handheld portable fire extinguishers and other fire fighting equipment. Fire-fighting activities that may result in potential exposure to high heat, smoke or toxic by-products of combustion should require NIOSH/MSHA- approved pressure-demand self-contained breathing apparatus with full facepiece and full protective clothing. Isolate area around container involved in fire. Cool tanks, shells, and containers exposed to fire and excessive heat with water. For massive fires the use of unmanned hose holders or monitor nozzles may be advantageous to further minimize personnel exposure. Major fires may require withdrawal, allowing the tank to burn.

**Hazardous combustion products**

Carbon monoxide, carbon dioxide and non-combusted hydrocarbons (smoke).

**Further information**

Dispose of fire debris and contaminated extinguishing water in accordance with official regulations.

**6. ACCIDENTAL RELEASE MEASURES****Emergency measures**

Evacuate nonessential personnel and remove or secure all ignition sources. Consider wind direction; stay upwind and uphill, if possible. Evaluate the direction of product travel, diking, sewers, etc. to confirm spill areas. Spills may infiltrate subsurface soil and groundwater; professional assistance may be necessary to determine the extent of subsurface impact.

**Personal precautions and protective equipment**

Response and clean-up crews must be properly trained and must utilize proper protective equipment (see Section 8).

**Environmental precautions**

Protect bodies of water by diking, absorbents, or absorbent boom, if possible. Do not flush down sewer or drainage systems, unless system is designed and permitted to handle such material. The use of fire fighting foam may be useful in certain situations to reduce vapors. The proper use of water spray may effectively disperse product vapors or the liquid itself, preventing contact with ignition sources or areas/equipment that require protection.

**Methods and materials for containment and cleaning up**

Carefully contain and stop the source of the spill, if safe to do so.

Take up with sand or other oil absorbing materials. Carefully shovel, scoop or sweep up into a waste container for reclamation or disposal. Caution, flammable vapors may accumulate in closed containers.

**QUICSEAL CONSTRUCTION CHEMICALS PTE LTD**

No. 7 Eunos Avenue 8A Eunos Industrial Estate Singapore 409460 Tel: (65) 6742 4466 Fax: (65) 6741 4666

Website: [www.quicseal.com](http://www.quicseal.com) Co.Reg. No.: 198201286W



## 7. HANDLING AND STORAGE

### Precautions for safe handling

Handle as a combustible liquid. Keep away from heat, sparks, excessive temperatures and open flame! No smoking or open flame in storage, use or handling areas. Bond and ground containers during product transfer to reduce the possibility of static-initiated fire or explosion.

### Conditions for safe storage, including any incompatibilities

Keep away from flame, sparks, excessive temperatures and open flame. Use approved vented containers. Keep containers closed and clearly labelled. Empty product containers or vessels may contain explosive vapors. Do not pressurize, cut, heat, weld or expose such containers to sources of ignition. Store in a well-ventilated area. Avoid storage near incompatible materials. Keep away from strong oxidizers.

## 8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

### Control parameters / Occupational Exposure Limits

None assigned.

### Appropriate engineering measure

No specific ventilation requirement noted.

### Personal protective equipment

#### Hand Protection

Gloves constructed of nitrile, neoprene, or PVC are recommended.

#### Eye Protection

Safety glasses or goggles are recommended where there is a possibility of splashing or spraying.

#### Skin Protection

Chemical protective clothing such as of E.I. DuPont TyChem®, Saranex® or equivalent recommended based on degree of exposure.

#### Respiratory Protection

A NIOSH/MSHA-approved air-purifying respirator with organic vapor cartridges or canister may be permissible under certain circumstances where airborne concentrations are or may be expected to exceed exposure limits or for odor or irritation. Protection provided by air-purifying respirators is limited. Use a positive pressure, air-supplied respirator if there is a potential for uncontrolled release, exposure levels are not known, in oxygen-deficient atmospheres, or any other circumstance where an air-purifying respirator may not provide adequate protection.

## QUICSEAL CONSTRUCTION CHEMICALS PTE LTD

No. 7 Eunos Avenue 8A Eunos Industrial Estate Singapore 409460 Tel: (65) 6742 4466 Fax: (65) 6741 4666

Website: [www.quicseal.com](http://www.quicseal.com) Co.Reg. No.: 198201286W



## 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance:	Clear to slightly brown liquid
Odour:	Smell of solvent
Flash Point:	35°C
Initial boiling point and boiling range:	140°C
Autoflammability:	Not Applicable
Explosive Properties (%):	Not Applicable
Specific Gravity:	1.01

## 10. STABILITY AND REACTIVITY

### Chemical stability

Stable at normal temperature.

### Possibility of hazardous reactions

Exothermic reaction with bases (e.g. caustic soda) ammonia, primary & secondary amines.

### Conditions to avoid

Avoid high temperatures, open flames, sparks, welding, smoking and other ignition sources.

### Incompatible materials

Keep away from strong oxidizers. May dissolve some plastics and rubber.

### Hazardous decomposition products

Carbon monoxide, carbon dioxide and non-combusted hydrocarbons (smoke).

## 11. TOXICOLOGICAL INFORMATION

This product has not been tested and all the toxicological statements have been derived from the respective components' available toxicity information.

### Acute toxicity

Experimental/calculated data:

LD50 (rat), oral: 4,294 mg/kg (the product may be harmful if swallowed.)

LD50 (rabbit), dermal: > 5,000 mg/kg (the product is not toxic/harmful in contact with skin)

LC50 (4 hr exposure): ~5 mg/L (the product is toxic if inhaled)

### Skin and Eye Irritation

This product may cause skin and eye irritation due to the following components:

Xylene, CAS No.: 1330-20-7 = Skin Irritant (Category 2) / Eye Irritant (Category 2)

4,4-Diphenylmethane Diisocyanate, CAS No.: 101-68-8 = Skin and Eye Irritant (Category 2)

## QUICSEAL CONSTRUCTION CHEMICALS PTE LTD

No. 7 Eunos Avenue 8A Eunos Industrial Estate Singapore 409460 Tel: (65) 6742 4466 Fax: (65) 6741 4666

Website: [www.quicseal.com](http://www.quicseal.com) Co.Reg. No.: 198201286W



**Respiratory / Skin sensitization**

The product component 4,4-Diphenylmethane Diisocyanate may cause an allergic skin reaction or asthma symptoms or breathing difficulties if inhaled.

**Reproductive toxicity**

Based on the evidence of weight reduction and hydrocephalus in fetuses at dosing levels not toxic to parent animals in mouse developmental toxicity tests, described in CERI-NITE Hazard Assessment (No. 62, 2004), EHC 190 (1997) and IRIS (2003), this product may damage fertility or the unborn child (Reproductive toxicity Category 1B)

**Carcinogenicity / Developmental toxicity**

The product has no known carcinogenic effect and is not expected to cause developmental toxicity.

**12. ECOLOGICAL INFORMATION**

The following ecological assessment is based on the available ecotoxicity information of the product's components.

**Acute toxicity to the aquatic environment**

Toxicity to fish: LC50 (96h): 3.3 mg/l, Rainbow trout (OECD Guideline 203, static)

This product is toxic to aquatic life (Acute toxicity to the aquatic environment Category 2)

**Environmental assessment**

This product is not known as biodegradable. Has potential to bio-accumulate.

**13. DISPOSAL CONSIDERATIONS****Description of waste residues and information on their safe handling & methods of disposal**

Dispose of the product through licensed hazardous waste collectors under Singapore regulations. Provide the hazardous waste collector the sufficient information on the various hazards of this product.

**Disposal of any contaminated packaging**

Dried material can be disposed off in authorized landfill site in accordance to national regulations. Container should be recycled after cleaning or dispose of the container through licensed hazardous waste collectors under Singapore regulations. Provide the hazardous waste collector the sufficient information on the various hazards of this product in this container.

#### 14. TRANSPORT INFORMATION

**Land Transport (ADR/RID):**

Shipping Name: PAINT-RELATED MATERIAL  
UN #: 1263  
Hazard Class: 3  
Packing Group: II

Label:

**Air Transport (IATA/ICAO):**

Shipping Name: PAINT-RELATED MATERIAL  
UN #: 1263  
Hazard Class: 3  
Packing Group: II

Label:

**Sea transport (IMDG):**

Shipping Name: PAINT-RELATED MATERIAL  
UN #: 1263  
Hazard Class: 3  
Packing Group: II  
EmS Number: F-E S-E  
Marine pollutant: No

Label:



#### 15. REGULATORY INFORMATION

**Applicable National Regulations**

This product is subject to the requirements in the following acts/regulations:

Workplace Safety and Health Act & Workplace Safety and Health (General Provisions) Regulations  
Environmental Protection and Management Act and Environmental Protection and Management  
Maritime and Port Authority of Singapore (Dangerous Goods, Petroleum and Explosives)

**International Regulations**

This product is classified as hazardous pursuant to the provision set forth in Directives 67/548/EEC and 1999/45/EC and/or EC Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of EC Regulation 1907/2006 and subsequent amendments.

#### 16. OTHER INFORMATION

The information and data contained herein are believed to be accurate and reliable; however, it is the user's responsibility to determine suitability of use. Since QUICSEAL Construction Chemicals Pte. Ltd. cannot know all of the uses to which its products may be put or the conditions of use; it makes no warranties concerning the fitness or suitability of its products for a particular use of purpose.

**QUICSEAL CONSTRUCTION CHEMICALS PTE LTD**

No. 7 Eunos Avenue 8A Eunos Industrial Estate Singapore 409460 Tel: (65) 6742 4466 Fax: (65) 6741 4666

Website: [www.quicseal.com](http://www.quicseal.com) Co.Reg. No.: 198201286W

