



QUICSEAL 207

Manhole Cover Seal

Description

QUICSEAL 207 is a butyl rubber self-adhesive seal for manhole and sewer application. It is a non-hardening, permanently flexible synthetic rubber sealant with strong adhesive properties.

Uses

QUICSEAL 207 is suitable for sealing gaps or joints in the following applications.

Sanitary and Stormwater Manhole
Underground Structures
Wastewater Structures

Advantages

Adheres to all surfaces like metal and concrete
Has a quick release from the release paper
Ease of compression during installation
Permanently flexible and does not harden upon exposure to weathering

Application

Ensure the surface is clean, dry and free of dirt, grease, oil or water. Cut convenient length from roll and remove release paper. Wrap the tape around joint overlapping each end. Knead the ends together to form a unified splice. Avoid stretching the tape during installation.

Typical Properties of QUICSEAL 207

Composition	Butyl Rubber Compound
Colour	Light Grey
Adhesive	Excellent to steel and concrete
Specific Gravity	1.78 – 1.88
Water Absorption	< 1.0%
Shelf Life	1 year in dry conditions at 20°C
Toxicity	No known hazards
Application	By hand direct from roll, removing paper
Application Temperature	5°C - 40°C
Service Temperature	-20°C to + 90°C
Surface Preparation	Contaminant free

Packaging

QUICSEAL 207 is supplied in lengths of

- 16mm x 3.8m (L) per roll

Other sizes maybe available upon request.

Storage

Store in original unopened packaging in cool and dry condition. Storage temperature shall be < 30°C. Avoid deformation.

Important Notes

The information set forth herein is furnished in good faith and is based on technical data that QUICSEAL considers to be reliable. This information is intended for used by persons having technical skill and at their own discretion and risk. Information contained in this product sheet conforms to the standard detail recommendations and specifications for the installation of QUICSEAL products as of the date of publication of this document. QUICSEAL makes no other warranties and assumes no liability, expressed or implied, as to the architecture, engineering or workmanship of any project. To ensure that you are using the latest, most complete information, contact QUICSEAL.

Reference No: QS 207/210920

QUICSEAL CONSTRUCTION CHEMICALS PTE LTD
www.quicseal.com