



QUICSEAL 632

Water-Based Stone Sealer

Description

QUICSEAL 632 is a specially formulated water based impregnator for the treatment of limestones, sandstones and all natural stone. While it provides water repellent properties to the treated natural stones, it also permits breathability, thus reducing the possible occurrences of efflorescence, staining, dirt pick up, oil stains and salt penetration.

Uses

QUICSEAL 632 allows in-depth penetration to most natural stones for internal and external application

- Marble, Terrazzo, Travertine, Granite, etc
- Concrete
- Mineral plasters
- Brickwork
- Sand-lime brickwork
- Paviments
- Mineral-based natural and artificial stone
- Precast concrete
- Cement boards
- Mortar Joints

Technical Data

Appearance	Transparent viscous liquid
Colour	Slightly brown
Odour	Slightly perfumed
pH (5% solution)	5 ~ 6
Specific gravity (20°C)	1.02
Flashing point	None
Oil resistance	Excellent
Resistance to Efflorescence	Excellent
Resistance to Alkalinity	Excellent
Weather Resistance	Excellent

Application

QUICSEAL 632 can be applied on the top surface and 4 edges with a short-haired roller, flat brush or a low pressure spray gun. Apply QUICSEAL 632 in 2-3 coats, with 3-4 hours between each coat. Remove any excess product from the surface with a soft and dry cloth and buff to achieve an original gloss. This is not necessary on rough surfaces such as terracotta or non-polishes natural stones. Protect the treated area for at least 3 hours for normal foot traffic. Keep dry for 24 hours for full cure.

For back treatment, use QUICSEAL 631.

Coverage

- Natural stones 8 - 12m²/ L per coat
- Terracotta 6.5 - 8.0m²/ L per coat

Packaging

QUICSEAL 632 is available in 5 and 25 litre tins.

Storage

Keep the tin closed and store in a cool place.

Shelf life

QUICSEAL 632 has a shelf life of at least 12 ~ 24 months, if stored in tightly closed original containers between 0°C ~ 30°C under shade.

Important Notes

The information set forth herein is furnished free of charge in good faith and is based on technical data that QUICSEAL considers to be reliable. This information is intended for used by persons having technical skill and at their own discretion and risk. Information contained in this product sheet conforms to the standard detail recommendations and specifications for the installation of QUICSEAL products as of the date of publication of this document. QUICSEAL makes no other warranties and assumes no liability, expressed or implied, as to the architecture, engineering or workmanship of any project. To ensure that you are using the latest, most complete information, please contact QUICSEAL.

Reference No. QS632/240221

QUICSEAL CONSTRUCTION CHEMICALS PTE LTD
www.quicseal.com

QUICSEAL – the professional's choice of quality products and systems for building construction