



QUICSEAL 408


uPVC TILE TRIM

Description

QUICSEAL 408 Tile Trim is made from high quality unplasticised polyvinyl chloride (uPVC) materials and offers high impact strength and surface hardness. QUICSEAL 408 is available in a wide range of colours to match popular sanitary fittings and tile colours.

Uses

- As a stopper / decorative finish at edge of tiles to provide better alignment of tiles.
- **Advantages**
- Perforated patterns in QUICSEAL Tile Trim sections ensure maximum anchorage under the tile adhesive or cement grout.
- Good fire (does not support combustion) and impact resistance.
- Does not support fungal growth
- Replace the conventional use of cove tiles that are prone to chipping and staining
- Easy to install with no sharp edges



Installation Instruction

1. Select the Tile Trim profile according to requirement.
2. Cut or mitre QUICSEAL 408 to required length with an aid of a cutter or sharp cutter.
3. Install the QUICSEAL 408 Tile Trim and ensure that it is securely embedded into the tile adhesive or cement grout.
4. Align the edge of the tiles with QUICSEAL 408 tile trim and ensure that the gap is constant along the entire length of the trim.
5. After laying the tiles, fill the joint between the tile and QUICSEAL 408 completely with grout.

Technical Data


| PROPERTY | UNIT | TEST METHOD | MPE-077 |
|-----------------------------------|------|-------------|-------------|
| Specific Gravity | - | ASTM D-792 | 1.35 ± 0.05 |
| Vicat Softening Point (1Kgf load) | °C | ASTM D-1525 | 90 ± 5 |
| Thermal Stability | Mins | B.S. 2782 | 30 ± 5 |

Tile Trim Profile

Dimensions

A = 28 mm

B = 9.5mm



Packing

Length : QUICSEAL 408 is available in lengths of 8 ft and 9 ft.
Pack size : 100 lengths per box

Important Notes

The information set forth herein is furnished in good faith and is based on technical data that QUICSEAL considers to be reliable. This information is intended for use by persons having technical skill and at their own discretion and risk. Information contained in this product sheet conforms to the standard detail recommendations and specifications for the installation of QUICSEAL products as of the date of publication of this document. QUICSEAL makes no other warranties and assumes no liability, expressed or implied, as to the architecture, engineering or workmanship of any project. To ensure that you are using the latest, most complete information, contact QUICSEAL

Reference No. QS408/270520

ARDEX-QUICSEAL SINGAPORE PTE. LTD.
www.ardex-quicseal.com