



QUICSEAL 719

Roof Mat

Description

QUICSEAL 719 Roof mat is a non-woven, spun bonded polyester fabric. Produced from an advanced technology, QUICSEAL 719 comprise of a continuous polyester filament which provides a high performance reinforcement for waterproofing system.

Advantages

- High tensile strength and lightweight.
- High dimensional stability against heat
- High heat resistance
- High UV resistance
- Resistant to rot
- Excellent wetting properties
- High air and water permeability
- Conforms easily to difficult substrate profiles

Uses

- As a reinforcement to a wide range of protective coatings, including modified bitumens, acrylics, polyurethane membranes & flexible cementitious membrane for roofing, pipe wrapping and tank lining, etc.
- Ideal for use in building up required thickness for coatings.

Storage

QUICSEAL 719 Roof mat must be stored in original packaging, away from series of ignition and away from direct sunlight.

Packing

QUICSEAL 719 Roof mat is available in 0.96m x 300 metre rolls.

Technical Data

Weight	30g/m ²
Thickness	0.14mm
Tensile strength (MD) (CD)	11kg/5cm 4kg/5cm
Elongation (MD) (CD)	25% 20%
Tear strength	0.90kg
Maximum width	4600mm

Important Notes

The information set forth herein is furnished free of charge in good faith and is based on technical data that QUICSEAL considers to be reliable. This information is intended for used by persons having technical skill and at their own discretion and risk. Information contained in this product sheet conforms to the standard detail recommendations and specifications for the installation of QUICSEAL products as of the date of publication of this document. QUICSEAL makes no other warranties and assumes no liability, expressed or implied, as to the architecture, engineering or workmanship of any project. To ensure that you are using the latest, most complete information, please contact QUICSEAL.

Reference No. QS719/210520

ARDEX-QUICSEAL SINGAPORE PTE. LTD.
www.ardex-quicseal.com