



QUICSEAL 631

Q – Porcelain

Description

QUICSEAL 631 is a ready to use, solvent based, water repellent impregnator with in-depth anti-salt peter and anti-mildew properties.

The product inhibits water absorption and the formation of mildew and limestone efflorescence for both indoor or outdoor flooring. It prevents moisture from rising from beneath the applied surface, thereby allowing the surfaces to “breathe” while leaving the surface colour unchanged.

The product enables the homogeneous absorption of wax-resinous of wax-resinous products and paste waxes on indoor surface.

Uses

QUICSEAL 631 is UV resistant and the in-depth penetration of the product creates a hydro-phobic surface barrier against corrosion caused by acid rains, marks of pollution and deposits of chemical agents.

The product can be used for both indoor or outdoor surfaces made of natural stone such as marble, granite, marble agglomerates, terracotta, cement, exposed brickwork and for any kind of surface, including those made of cement where an alkali resistant barrier is required.

Application

Apply QUICSEAL 631 on perfectly clean and dry surface using a brush or a roller and coat over the joints evenly and thoroughly.

Precaution

QUICSEAL 631 should not be applied during the hottest hours of the day where the surface will be heated up. No rain should be forecast for at least 2 days following QUICSEAL 631 treatment.

Not recommended to be applied on black or dark coloured surfaces (ie. Honed, flamed/ bush hammered, sand-blasted or on chiseled). It is advisable to conduct a sample test to check for any colour changes to the materials to be treated prior to actual application.

Coverage

Polished stones – 30 to 40 m² per litre per coat

Natural finished stones – 15 to 20 m² per litre per coat

Testing the product

After the application of the product in the laboratory in order to check the resistance of the product against stains, allow to dry the QUICSEAL 631 for 24 hours then apply the stains.

Maintenance

For regular maintenance clean the surface with QUICSEAL 653 or a neutral pH cleaner.

Packing

QUICSEAL 631 is supplied in 1 litre, 5 litres and 25 litres tin

Shelf life

12 months when kept in a cool and ventilated place in the original packaging

Health & Safety

The product is flammable. Gloves and facemask should be worn. May irritate eyes and skin. Any splashes to the skin or eyes should be rinsed off with clean water for at least 15 minutes. In the event of prolonged irritation, seek medical advice. Use in well ventilated environment. Please refer to Material Safety Datasheet for more information.

Accidental Spillage & Waste Disposal Method

In case of product leakage or spillage, clean up most of the product by using sand, sawdust etc to absorb all residues. Store these residues in plastic tank and arrange for disposal by specialized company.

Important Notes

The information set forth herein is furnished free of charge in good faith and is based on technical data that QUICSEAL considers to be reliable. This information is intended for used by persons having technical skill and at their own discretion and risk. Information contained in this product sheet conforms to the standard detail recommendations and specifications for the installation of QUICSEAL products as of the date of publication of this document. QUICSEAL makes no other warranties and assumes no liability, expressed or implied, as to the architecture, engineering or workmanship of any project. To ensure that you are using the latest, most complete information, please contact QUICSEAL

Reference No. QS631/3240520

ARDEX-QUICSEAL SINGAPORE PTE. LTD.
www.ardex-quicseal.com