



QUICSEAL 635

Stone Enhancer

Description

QUICSEAL 635 is a solvent based, stain repellent impregnator cum stone enhancer for the protective treatment of natural or agglomerate stones.

When applied, the product protects the surface against dirt, grease, oil, water, etc. while enhancing the colour of the stone.

QUICSEAL 635 imparts a warm tone to the treated stones and also enhances the appearance of the natural veins found in the material.

Uses

QUICSEAL 635 is suitable as a protective treatment for marbles, granites, agglomerates, stones and for honed or smooth surfaces.

Advantages

- Oil, dirt and water repellent.
- Protects and enhances the appearance of the stone.
- Suitable for internal and external surface.

Technical Data

Appearance	Transparent viscous liquid
Colour	Amber
pH (5% solution)	N/A
Specific gravity (20°C)	0,850 gr./cc
Flashing point (ASTM D 56)	46°C

Application

QUICSEAL 635 can be applied with a lambswool or a brush. On honed surfaces, apply sufficient amount of the product to be coated and avoid excess application.

Maintenance

For regular maintenance clean the surface with a neutral pH cleaner.

Fortuitous leakage and waste disposal method

In case material is released or spilled, clean up the most of the product. Absorb all residues with sand, sawdust etc. Store the residue in plastic tank and call for a specialized company.

Packaging

QUICSEAL 635 is supplied in 5 litres bottles.

Shelf life

12-24 months

Coverage

12-18 sqm / ltr depending on material porosity

Storage

Keep the tin closed and store in a cool place.

Important Notes

The information set forth herein is furnished free of charge in good faith and is based on technical data that QUICSEAL considers to be reliable. This information is intended for used by persons having technical skill and at their own discretion and risk. Information contained in this product sheet conforms to the standard detail recommendations and specifications for the installation of QUICSEAL products as of the date of publication of this document. QUICSEAL makes no other warranties and assumes no liability, expressed or implied, as to the architecture, engineering or workmanship of any project. To ensure that you are using the latest, most complete information, please contact QUICSEAL.

Reference No. QS635/230520

ARDEX-QUICSEAL SINGAPORE PTE. LTD.
www.ardex-quicseal.com