



QUICSEAL 658

Q – Cotto Alkaline Cleaner

Description

QUICSEAL 658 is a heavy duty, liquid compound detergent with slight alkaline base (PH around 8-9) formulated to be used in various circumstances. It can be used in the process for the removal of dark stains caused by salts, which is usually impossible to remove with acid detergents as well as to clean greasy surfaces, removing waxes or in conjunction with QUICSEAL 659 to remove old or wrongly executed treatments, wax coats, grease.

Uses

QUICSEAL 658 has excellent performance on a wide range of floorings such as porcelain stoneware, ceramic, marble, granite, marble agglomerate, natural stones, synthetic material and cement etc.

Note: Do not use on textile flooring or non-varnished wood.

Application

Dilute 50 to 100 grams of QUICSEAL 658 in 10 litres of water. Apply the solution on the floor and leave it for about 5 minutes. Clean the floor by using a rag or floor cleaning machine, gently rinse and dry to complete the process.

Coverage

- Porcelain material – 35 to 50 sqm per litre
- Natural stones – 20 to 35 sqm per litre
(May vary according to the type of material and dirt to be removed)

Packing

QUICSEAL 658 is supplied in 1 litre container and 5 litres drum.

Shelf life

12 months when kept in a cool and ventilated place in the original packaging

Caution

CORROSIVE PRODUCT. QUICSEAL 658 may cause serious burns. It is caustic for eyes and skin. Use gloves, rubber shoes and glasses. Avoid contact with eyes and skin. In case of contact with eyes wash with plenty of water and call for a doctor. Keep out of children's reach.

Fortuitous Leakage and Waste Disposal Method

In case material is released or spilled, clean up most of the product. Store the residue in plastic tanks, neutralize with a solution of hydrochloric acid adjusting the pH to 6-7 then send to an appropriate water conditioner or call for a specialized company.

Important Notes

The information set forth herein is furnished free of charge in good faith and is based on technical data that QUICSEAL considers to be reliable. This information is intended for used by persons having technical skill and at their own discretion and risk. Information contained in this product sheet conforms to the standard detail recommendations and specifications for the installation of QUICSEAL products as of the date of publication of this document. QUICSEAL makes no other warranties and assumes no liability, expressed or implied, as to the architecture, engineering or workmanship of any project. To ensure that you are using the latest, most complete information, please contact QUICSEAL.

Reference No. QS658/230520

ARDEX-QUICSEAL SINGAPORE PTE. LTD.
www.ardex-quicseal.com