



QUICSEAL 665

Q - Shine

Description

QUICSEAL 665 is a fluid especially made for the maintenance of quartz agglomerates due to traffic. The maintenance with this product will re-establish a very good sheen giving to old and dull surface and improves resistance to trafficking.

Technical Data

Appearance	Cream
Color	White
Odour	Typical
pH	Neutral
Specific gravity (20°C)	1.05
Flash Point (ASTM D 56)	None

Application

Shake well before use. On large areas, pour about 20 ~ 30 g of the product on the surface and work with a polishing machine with white pad. Begin the polishing at 150 rounds/minute and continue until the product dries.

For first time polishing, 2 ~ 3 applications may be required with a few drops water added during the polishing.

Caution

May cause irritation to eyes and skin. Keep away from children's reach.

Packaging

QUICSEAL 665 is supplied in 5 litre tins.

Shelf Life

12 ~ 24 months in original sealed packing kept in cool and dry place.

Fortuitous leakage and waste disposal method

In case material is released or spilled, clean up the most of the product and vacuum up the residues. Store the residues coming from polishing operations and commit to a specialized company.

Important Notes

The information set forth herein is furnished free of charge in good faith and is based on technical data that QUICSEAL considers to be reliable. This information is intended for used by persons having technical skill and at their own discretion and risk. Information contained in this product sheet conforms to the standard detail recommendations and specifications for the installation of QUICSEAL products as of the date of publication of this document. QUICSEAL makes no other warranties and assumes no liability, expressed or implied, as to the architecture, engineering or workmanship of any project. To ensure that you are using the latest, most complete information, please contact QUICSEAL.

Reference No. QS665/230520

ARDEX-QUICSEAL SINGAPORE PTE. LTD.
www.ardex-quicseal.com