



QUICSEAL 670

Yellow Polishing Powder

Description

QUICSEAL 670 is a compound in the form of powder ideal for the polishing of marbles, travertines, limestone, agglomerates and any type of material containing calcium carbonate.

Advantages

QUICSEAL 670 is easy to use and contributes to a very highly polished sheen to the treated surface.

Technical data

Appearance	Powder
Colour	Yellow
Odor	Odorless
Flash point	Non-flammable
PH Value	3-4 ± 0.5
Density @20°C	1.2 g/ml

How to apply

The surface to be treated with QUICSEAL 670 must be free of wax and superficial film.

- i) Pour a few drops of water for every 1 to 2m² of stone surface.
- ii) Apply 1-2 spoonfuls in the centre of the area and start to polish the surface with a floor machine (use the white or red buffing pad).
- iii) For best results, buff the surface such that a fluid cream is formed. If the cream thickens while buffing, add a few drops of water to maintain the fluidity.
- iv) Maintain buffing for 2-3minutes per m² of stone surface.
- v) Continue with this method until the whole of the area is polished.

Consumption

Subject to actual usage on site.

Packaging

5kg and 20kg pail

Shelf Life

When stored in a dry and cool place, the shelf life of QUICSEAL 670 is 12 -24 months.

Precautions

Gloves and goggles should be worn. Any splashes to the skin or eyes should be washed off with clean water. In the event of prolonged irritation, seek medical advice. Powder products should be handled to minimize dust formation. Use a light mask if excessive dusting is unavoidable. Harmful if swallowed. Keep out of children's reach. Please refer to the Material Safety Data Sheet for more information.

Important Notes

The information set forth herein is furnished in good faith and is based on technical data that QUICSEAL considers to be reliable. This information is intended for use by persons having technical skill and at their own discretion and risk. Information contained in this product sheet conforms to the standard detail recommendations and specifications for the installation of QUICSEAL products as of the date of publication of this document. QUICSEAL makes no other warranties and assumes no liability, expressed or implied, as to the architecture, engineering or workmanship of any project. To ensure that you are using the latest, most complete information, contact QUICSEAL

Reference No. QS670/230520

ARDEX-QUICSEAL SINGAPORE PTE. LTD.
www.ardex-quicseal.com