



QUICSEAL 633T

Superseal

Description

QUICSEAL 633T is a solvent-based, highly penetrative impregnator into all building materials including natural stones for internal and external areas. It does not change the color of the material due to its unique blend of organic solvents and small molecules size. It protects the treated stones from oil stains, water, efflorescence, dirt pick up and graffiti.

Use

QUICSEAL 633T allows in-depth penetration to most natural stones and masonry surface such as:

- Limestone/Sandstone
- Marble
- Granite
- Slate
- Travertine
- Roof Tiles

Advantages

- Water and oil repellent
- Protection against rising damp marks
- No significant change in appearance on natural stones (patch test to be carry out on site)
- Internal and external application
- Breathable

Application

QUICSEAL 633T can be applied on the top surface and 4 edges by brush, low pressure sprinklers with 0.5mm nozzle, airless spray spray gun to clean, dry, cold surfaces not exposed to sunlight nor during the hottest hours of the day. Spraying shall be done about 20cm away from the surface to be treated. Any excess QUICSEAL 633T can be removed using a clean white cloth moistened with the product itself or a brush equipped with a soft disk.

Two coats may be required depending on porosity of materials, leaving 2 - 3 hours between each coat. When used outdoors, apply only when good weather is forecasted and is expected to hold well for 12 hours.

Shelf Life

QUICSEAL 633T has a shelf life of at least 12 months, if stored in tightly closed original containers between 0°C – 30°C under shade.

Coverage

QUICSEAL 633T can be applied at an approximate rate of 10-14 m²/litre.
Note: Consumption may vary depending on the porosity of the substrate.

Packaging

QUICSEAL 633T is available in 1, 5 and 25 litre tins.

Precautions

It is always good to test an inconspicuous area first to ascertain any change in colour of the materials to be treated. Cover windows and surrounding vegetation with plastic sheets during application. Ensure that the rollers and surface are clean prior to application.

Health & Safety

Gloves and facemasks should be worn. Any splashes to the skin or eyes should be washed off with clean water. See medical advice immediately. In the event of prolonged irritation, seek medical advice. Use in well ventilated environment and do not inhale the fumes. QUICSEAL 633T is highly flammable. Do not smoke and keep away from heat sources, flames and sparks. Switch off engines nearby. Keep out of reach of children. QUICSEAL 633T contains ethyl acetates. Refer to Material Safety Data Sheet for more information.

Important Notes

The information set forth herein is furnished free of charge in good faith and is based on technical data that QUICSEAL considers to be reliable. This information is intended for used by persons having technical skill and at their own discretion and risk. Information contained in this product sheet conforms to the standard detail recommendations and specifications for the installation of QUICSEAL products as of the date of publication of this document. QUICSEAL makes no other warranties and assumes no liability, expressed or implied, as to the architecture, engineering or workmanship of any project. To ensure that you are using the latest, most complete information, please contact QUICSEAL.

Reference No. QS633T/110522

ARDEX-QUICSEAL SINGAPORE PTE. LTD.
www.ardex-quicseal.com

QUICSEAL – the professional's choice of quality products and systems for building construction