



# QUICSEAL 634

## Stone Impregnator

### Description

QUICSEAL 634 is a water-based, water repellent impregnator that does not change the aesthetics of the surface and substrate. When applied, the product gives the surface an invisible protection and resistance against water, mold built-up and wear due to weathering factors.

### Uses

QUICSEAL 634 allows in-depth penetration to most natural stones for internal and external application

- Limestone
- Marble
- Granite
- Sandstone
- Bricks
- Roof Tiles
- Concrete

### Advantages

- Dirt and water repellent.
- Protects and does not alter the appearance of the stone.
- Can be applied on all six sides of marbles

### Application

#### Surface Preparation

Surface must be free of any contamination such as waxes, oils, loose concrete, dirt, curing compounds or any other substance that may hinder penetration of the substrate.

QUICSEAL 634 can be applied on all six sides of natural stones with a short-haired roller, flat brush or a airless gun at low pressure. Two coats may be required depending on porosity of materials, leaving 3 - 4 hours between each coat. It is advisable to protect the treated surface from rain for 24 hours after application.

#### Note:

1. Do not apply QUICSEAL 634 on surfaces directly exposed to sunlight or during noon when it is the hottest hours of the day.
2. Do a spot test to check for color change on the stone to be treated.
3. For treatment on all six sides of natural stones, use compatible cementitious tile adhesives having the classification C2ES1 or higher

#### Accidental leakage and waste disposal method

In case material is released or spilled, clean up most of the product. Absorb all residues with sand, sawdust etc. Store the residue in plastic tank and call for a specialized company.

#### Coverage

30m<sup>2</sup> per litre per coat for polished stones  
15 to 20m<sup>2</sup> per litre per coat for natural finished stones

#### Packaging

QUICSEAL 634 is supplied in 5 litres drum and 25 litres drum.

#### Shelf life

QUICSEAL 634 has a shelf life of 12 months, if stored in tightly closed original containers between 5°C ~ 30°C under shade.

#### Storage

Keep the tin closed and store in a cool place.

#### Important Notes

The information set forth herein is furnished free of charge in good faith and is based on technical data that QUICSEAL considers to be reliable. This information is intended for used by persons having technical skill and at their own discretion and risk. Information contained in this product sheet conforms to the standard detail recommendations and specifications for the installation of QUICSEAL products as of the date of publication of this document. QUICSEAL makes no other warranties and assumes no liability, expressed or implied, as to the architecture, engineering or workmanship of any project. To ensure that you are using the latest, most complete information, please contact QUICSEAL

Reference No. QS634/060522

ARDEX-QUICSEAL SINGAPORE PTE. LTD.  
[www.ardex-quickseal.com](http://www.ardex-quickseal.com)