



QUICSEAL 637

Solvent-Based Impregnator

Description

QUICSEAL 637 is a solvent-based, in-depth water repellent impregnator that penetrates all absorbent building materials including natural stones for internal and external areas. Generally, it does not change the color of the material and protects the treated stones from UV rays and efflorescence.

Uses

QUICSEAL 637 allows in-depth penetration to most natural stones for internal and external application

- Concrete
- Limestone
- Sandstone
- Terrazzo
- Roof Tiles
- Slate
- Granite

Advantages

- Dirt and water repellent.
- Protects and does not alter the appearance of the stone.
- Can be applied on all six sides of marbles: both honed and polished
- Highly resistant to efflorescence

Application

Surface Preparation

Surface must be dry and free of any contamination such as waxes, oils, loose concrete, dirt, curing compounds or any other substance that may hinder penetration of the substrate.

QUICSEAL 637 can be applied on all six sides of natural stones with a short-haired roller, flat brush or a airless gun at low pressure. Two coats may be required depending on porosity of materials, leaving 3 - 4 hours between each coat. Curing time is 24 hours.

Note:

1. Do not apply QUICSEAL 637 on surfaces directly exposed to sunlight or during noon when it is the hottest hours of the day.
2. Do a spot test to check for color change on the stone to be treated.
3. For treatment on all six sides of natural stones, use compatible cementitious tile adhesives having the classification C2ES1 or higher

Accidental leakage and waste disposal method

In case material is released or spilled, clean up most of the product. Absorb all residues with sand, sawdust etc. Store the residue in plastic tank and call for a specialized company.

Packaging

QUICSEAL 637 is supplied in 5 litres pail and 25 litres pail.

Shelf life

QUICSEAL 637 has a shelf life of 12 months, if stored in tightly closed original containers between 0°C – 30°C under shade

Coverage

10 to 20m² per litre per coat for natural finished stones

Storage

Keep the tin closed and store in a cool place.

Important Notes

The information set forth herein is furnished free of charge in good faith and is based on technical data that QUICSEAL considers to be reliable. This information is intended for used by persons having technical skill and at their own discretion and risk. Information contained in this product sheet conforms to the standard detail recommendations and specifications for the installation of QUICSEAL products as of the date of publication of this document. QUICSEAL makes no other warranties and assumes no liability, expressed or implied, as to the architecture, engineering or workmanship of any project. To ensure that you are using the latest, most complete information, please contact QUICSEAL

Reference No. QS637/060522

ARDEX-QUICSEAL SINGAPORE PTE. LTD.
www.ardex-quicseal.com

QUICSEAL – the professional's choice of quality products and systems for building construction